

Uponor Wipex reducer male x female G2-G1

1018371



About Uponor Wipex reducer male x female

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex reducer male x female G2-G1

1018371



Technical data

Item no EAN	7331541099042
Item no GTIN	07331541099042
Item no VVS	087836165
RSK no.	2410638
Item no NRF	8360733
Item no LVI	1934040
Item (unit of measurement)	pce
Length (l)	41 mm
Packaging Quantity 1	1
Packaging Quantity 3	15
Packaging GTIN PL1	06414905437986
Packaging GTIN PL3	06414905446803
Item Unit Length	42
Item Unit Height	80
Item Unit Weight	0,406
Item Unit Width	38

Technical documents

[Download documents here](#) 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb