

Uponor Wipex reducer male x female G3-G1 1/4

1018375



About Uponor Wipex reducer male x female

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application


- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex reducer male x female G3-G1 1/4

1018375



Technical data

Item no EAN	7331541098991
Item no GTIN	07331541098991
Item no VVS	087836178
RSK no.	2410642
Item no NRF	8360737
Item no LVI	1934070
Item (unit of measurement)	pce
Length (l)	51 mm
Packaging Quantity 1	1
Packaging Quantity 3	10
Packaging GTIN PL1	06414905438020
Packaging GTIN PL3	06414905446841
Item Unit Length	105
Item Unit Height	55
Item Unit Weight	1,04
Item Unit Width	105

Technical documents

[Download documents here](#) 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb