

## Uponor Vario PLUS manifold flowmeter FM 3x3/4 Euro

1030583



### About Uponor Vario PLUS manifold flowmeter

#### Specification

- Modular fibre glass reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- connection right or left with flat sealing or connection from below with optional elbowset
- supply with lockshield (LS) valve for balancing with adjusting ring or supply with Flowmeter (FM) for balancing
- shut-off and flow view
- adjusting ring for balancing without tools
- prepared places for room name labels
- return with valves and caps, prepared for actuators
- loop connection G3/4" eurocone
- loop pitch 50 mm
- header pitch 225 mm

Actuator:

- NC (normally closed) = closes without power

#### Application

- for underfloor heating and cooling
- combineable with actuators MT 30x1,5

#### Certification

- CE

## Uponor Vario PLUS manifold flowmeter FM 3x3/4 Euro

1030583



### Technical data

Item no EAN	4016203841339
Item no GTIN	04016203841339
Item (unit of measurement)	set
Length (l)	174 mm
Length (l1)	150 mm
Length (l2)	119 mm
Length (l3)	63 mm
Z-measurement b	50 mm
z3	50 mm
Packaging Quantity 1	1
Packaging Quantity 4	174
Packaging GTIN PL1	06414905265008
Packaging GTIN PL4	06414905265015
Item Unit Length	170
Item Unit Height	180
Item Unit Weight	0,758
Item Unit Width	45

### Technical documents

Download documents here

#### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)