

Uponor Vario PLUS manifold flowmeter FM 6x3/4 Euro

1030585



About Uponor Vario PLUS manifold flowmeter

Specification

- Modular fibre glass reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- connection right or left with flat sealing or connection from below with optional elbowset
- supply with lockshield (LS) valve for balancing with adjusting ring or supply with Flowmeter (FM) for balancing
- shut-off and flow view
- adjusting ring for balancing without tools
- prepared places for room name labels
- return with valves and caps, prepared for actuators
- loop connection G3/4" eurocone
- loop pitch 50 mm
- header pitch 225 mm

Actuator:

- NC (normally closed) = closes without power

Application

- for underfloor heating and cooling
- combineable with actuators MT 30x1,5

Certification

- CE

Uponor Vario PLUS manifold flowmeter FM 6x3/4 Euro

1030585



Technical data

Item no EAN	4016203841360
Item no GTIN	04016203841360
Item (unit of measurement)	set
Length (l)	324 mm
Length (l1)	300 mm
Length (l2)	119 mm
Length (l3)	63 mm
Z-measurement b	50 mm
z3	50 mm
Packaging Quantity 1	1
Packaging Quantity 4	93
Packaging GTIN PL1	06414905265046
Packaging GTIN PL4	06414905265053
Item Unit Length	320
Item Unit Height	180
Item Unit Weight	1,49
Item Unit Width	45

Technical documents

Download documents here

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb