


Uponor S-Press tee PPSU 75-75-75

1032888

- Fast installation with easy bevel and without calibration
- Colour code



About Uponor S-Press tee PPSU

Specification

- with fixed press sleeve
- stop ring
- test safety

Application


- Heating systems (high temperature radiators) - where the water temperature does not continuously exceed 80°C, 10 bar (Conditions to application Class 5 - BS EN ISO 21003-1:2008). The maximum short-term malfunction temperature is 100°C for an accumulative 100 hours over the working life of the system. (Heating systems must be installed with room and water temperature controls in accordance with the current Building Regulations Parts L1 (Energy – Dwellings) and L2 (Energy – Non Dwellings) for England and Wales, or an equivalent national standard for Scotland or Republic of Ireland)
 - Cold water domestic services: 0°C to 20°C where the water temperature does not exceed 20°C, 16bar
 - Hot water domestic services: 20°C to 70°C where the water temperature does not continuously exceed 70°C, 10 bar (Conditions to application Class 2 - BS EN ISO 21003-1:2008). The maximum short-term malfunction temperature is 95°C for an accumulative 100 hours over the working life of the system.
 - Uponor multi-layer pipe can be used for DHW recirculating systems, provided the operating temperatures and pressures do not exceed the maximum conditions detailed under 'Domestic Services'
 - Chilled water: -10°C to 10°C,10 bar. If risk of damage from freezing, a suitable anti-freeze additive must be used. Any additive must be suitable for use with Polyethylene, PPSU, EPDM and CW625N brass
- if not different mentioned:
- Male and female threads acc.to EN 10226-1.

Certification

- WRAS : 2010907 - Uponor S-Press 12 & 14mm, MLC
- WRAS : 2109108 - S-Press & RS Modular 40-110mm, MLC
- KIWA – UK water Regulation 4
- Manufacturing is in accordance with the international quality standard ISO 9001 and environmental standard ISO 14001

Uponor S-Press tee PPSU 75-75-75

1032888



Technical data

Item no EAN	6414905220878
Item no GTIN	06414905220878
Item no VVS	087442175
RSK no.	1808042
Item no NRF	5114371
Item no LVI	1720157
Item (unit of measurement)	pce
Length (l1)	108 mm
Length (l2)	107 mm
Length (l3)	108 mm
z2	47 mm
z3	47 mm
Packaging Quantity 1	1
Packaging Quantity 4	150
Packaging GTIN PL1	06414905281299
Packaging GTIN PL4	06414905281305
Item Unit Length	215
Item Unit Height	84
Item Unit Weight	0,941
Item Unit Width	151

Technical documents

[Download documents here](#)

UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb