


## Uponor S-Press tee reducer PPSU 75-32-75

1032892

- Fast installation with easy bevel and without calibration
- Colour code



### About Uponor S-Press tee reducer PPSU

#### Specification

- with fixed press sleeve
- stop ring
- test safety

#### Application

-Heating systems (high temperature radiators) - where the water temperature does not continuously exceed 80°C, 10 bar (Conditions to application Class 5 - BS EN ISO 21003-1:2008). The maximum short-term malfunction temperature is 100°C for an accumulative 100 hours over the working life of the system. (Heating systems must be installed with room and water temperature controls in accordance with the current Building Regulations Parts L1 (Energy – Dwellings) and L2 (Energy – Non Dwellings) for England and Wales, or an equivalent national standard for Scotland or Republic of Ireland)

-Cold water domestic services: 0°C to 20°C where the water temperature does not exceed 20°C, 16bar

-Hot water domestic services: 20°C to 70°C where the water temperature does not continuously exceed 70°C, 10 bar (Conditions to application Class 2 - BS EN ISO 21003-1:2008). The maximum short-term malfunction temperature is 95°C for an accumulative 100 hours over the working life of the system.

-Uponor multi-layer pipe can be used for DHW recirculating systems, provided the operating temperatures and pressures do not exceed the maximum conditions detailed under 'Domestic Services'

-Chilled water: -10°C to 10°C, 10 bar. If risk of damage from freezing, a suitable anti-freeze additive must be used. Any additive must be suitable for use with Polyethylene, PPSU, EPDM and CW625N brass

if not different mentioned:

- Male and female threads acc.to EN 10226-1.

#### Certification

-WRAS : 2010907 - Uponor S-Press 12 & 14mm, MLC


-WRAS : 2109108 - S-Press & RS Modular 40-110mm, MLC

-KIWA – UK water Regulation 4

-Manufacturing is in accordance with the international quality standard ISO 9001 and environmental standard ISO 14001

## Uponor S-Press tee reducer PPSU 75-32-75

1032892



### Technical data

Item no EAN	6414905220915
Item no GTIN	06414905220915
Item no VVS	087442170
RSK no.	1808046
Item no NRF	5114375
Item no LVI	1720161
Item (unit of measurement)	pce
Length (l1)	108 mm
Length (l2)	74 mm
Length (l3)	108 mm
z2	45 mm
z3	47 mm
Packaging Quantity 1	1
Packaging Quantity 4	150
Packaging GTIN PL1	06414905281312
Packaging GTIN PL4	06414905281329
Item Unit Length	215
Item Unit Height	84
Item Unit Weight	0,711
Item Unit Width	118

### Technical documents

Download documents here

UK

T +44 (0)1923 927000  
E enquiries.uk@uponor.com

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)