


Uponor Siccus 12 panel, feeder 12mm 1200x250x15mm c/c40mm PS

1034340

- installation panel with grooves
- for feeders of radiant loops
- EPS Compressive strength: = 150 kPa
- R=0.4 m²K/W



About Uponor Siccus 12 panel, feeder

Specification

- Siccus underfloor heating panel system, consists of EPS (HBCD-free) boards acc. EN 13163 with Aluminium heat spreaders.
- EN 13501-1 fire classification: class E
- for installations with pipe c-c 125mm
- for pipe dim 12mm

Application


- radiant underfloor heating and cooling
- for dry-build installations
- very low construction height

Certification

- DIN CERTCO: 7F316-F

Uponor Siccus 12 panel, feeder 12mm 1200x250x15mm c/c40mm PS

1034340



Technical data

Item no EAN	7321500028701
Item no GTIN	07321500028701
Item no VVS	339262042
RSK no.	2418555
Item no NRF	8362509
Item no LVI	2023562
Item (unit of measurement)	pce
Packaging Quantity 1	10
Packaging Material short PL1	PAP
Packaging Material PL1	Corrugated fibreboard
Packaging GTIN PL1	06414905457595
Item Unit Length	1200
Item Unit Height	15
Item Unit Weight	0,11
Item Unit Width	245

Technical documents

Download documents here

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb