


Uponor Ecoflex Supra PLUS cable set S2

1042311

- Set 2 connection of the self regulating frost protection cable
- Frost protection cable tee and cable end termination



About Uponor Ecoflex Supra PLUS cable set S2

Specification

- Flexible, pre-insulated, self-compensating plastic pipe system
- Medium pipe: Polyethylene PE80, PN 12,5 (SDR 11) or PE100, PN 16 (SDR 11) black with blue stripes or PE 100, PN 16 (SDR 11) black with blue layer and new in PE100 RC, PN16 (SDR11) black with blue stripes
- Cable: self-regulating frost protection cable, nominal power output 10W/m at 5°C, Electricity feed from one supply point max. 150 m
- Conduit pipe: PE tube to insert a sensor and to measure the temperature.
- Insulating material: closed-cell PE-X foam, permanently elastic, ageing-resistant
- Casing pipe: Corrugated polyethylene (HDPE)

Application


- Transport of cold potable water or pressure drainage in locations where there is a risk of freezing for buried installations.
- Operating temperature +20°C
- Static verification for heavy traffic load of 60 tons

Certification

- Approvals should be checked by local responsible person

Uponor Ecoflex Supra PLUS cable set S2

1042311



Technical data

Item no EAN	6414905450527
Item no GTIN	06414905450527
Item no VVS	070699102
Item no NRF	8360946
Item no LVI	1846026
Item (unit of measurement)	pce
Packaging Quantity 1	1
Packaging GTIN PL1	06414900325004
Item Unit Length	254
Item Unit Height	44
Item Unit Weight	0,038
Item Unit Width	44

Technical documents

Download documents here

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb