

## Uponor Wipex swivel union G1 1/4-G1

**1045456**

- Rotatable double nipple
- Cylindric thread G" for O-ring sealing
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DR = dezincification resistance brass



### About Uponor Wipex swivel union

#### Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

#### Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

#### Certification

- Approvals should be checked by local responsible person

## Uponor Wipex swivel union G1 1/4-G1

1045456



## Technical data

Item no EAN	7331541201766
Item no GTIN	07331541201766
Item no VVS	087534151
RSK no.	2410702
Item no NRF	8360802
Item no LVI	1937001
Item (unit of measurement)	pce
Length (l)	50 mm
Length (l1)	12 mm
Length (l2)	21 mm
Packaging Quantity 1	1
Packaging Quantity 3	20
Packaging Quantity 4	1200
Packaging GTIN PL1	06414905459506
Packaging GTIN PL3	06414905448289
Packaging GTIN PL4	06414905492732
Item Unit Length	55
Item Unit Height	52
Item Unit Weight	0,33
Item Unit Width	52

## Technical documents

[Download documents here](#) 

UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)[www.uponor.com/en-gb](http://www.uponor.com/en-gb)