

Uponor Vario PLUS insulation kit

1063207

- Insulation thickness 19 mm, 0,038 W/mK
- Length 665 mm
- Fire classification BL-s3,do (EN 13501-1)



About Uponor Vario PLUS insulation kit

Specification

- Modular fibre glass reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- connection right or left with flat sealing or connection from below with optional elbowset
- supply with lockshield (LS) valve for balancing with adjusting ring or supply with Flowmeter (FM) for balancing
- shut-off and flow view
- adjusting ring for balancing without tools
- prepared places for room name labels
- return with valves and caps, prepared for actuators
- loop connection G3/4" eurocone
- loop pitch 50 mm
- header pitch 225 mm

Actuator:

- NC (normally closed) = closes without power

Application

- for underfloor heating and cooling
- combineable with actuators MT 30x1,5

Certification

- CE

Uponor Vario PLUS insulation kit

1063207



Technical data

Item no EAN	4021598124400
Item no GTIN	04021598124400
Item no VVS	087604200
RSK no.	2419859
Item (unit of measurement)	set
Packaging Quantity 3	1
Packaging GTIN PL3	06414905450404
Item Unit Length	655
Item Unit Height	55
Item Unit Weight	0,32
Item Unit Width	190

Technical documents

Download documents here

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb