

## Uponor Wipex swivel union G1 1/4 120mm

**1065442**

- Rotatable double nipple
- Cylindric thread G" for O-ring sealing
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DR = dezincification resistance brass



### About Uponor Wipex swivel union

#### Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

#### Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

#### Certification

- Approvals should be checked by local responsible person

## Uponor Wipex swivel union G11/4 120mm

1065442



### Technical data

Item no EAN	4021598131071
Item no GTIN	04021598131071
Item (unit of measurement)	pce
Length (l)	120 mm
Length (l1)	16 mm
Length (l2)	21 mm
Packaging Quantity 1	1
Packaging Quantity 3	8
Packaging GTIN PL1	06414905484652
Packaging GTIN PL3	06414905484669
Item Unit Length	50
Item Unit Height	120
Item Unit Weight	0,663
Item Unit Width	50

### Technical documents

Download documents here

#### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)