

Uponor Vario actuator retrofit set A-XXX 24V, NC, 1W

1083575

- 24V actuator retrofit set
- incl. 3 bayonet manifold valve adaptor rings, mounting instructions
- interface between existing third-party manifolds and Uponor Smatrix control system
- compatible to 80% of existing third-party manifolds
- open/closed indicator
- NC (normally closed) = closes without power
- first open function
- Autobalancing functionality for new and retrofit installations
- temperature range: 0°C...60°C
- height: 58mm + adaptor ring
- color: blue
- adaption list can be found at: www.uponor.com/download-centre
- stroke length: 5mm
- connection cable: 2x 0.75mm² x 1m
- Ucoil: 24V/50Hz
- Pcoil: 1W
- diameter: 44.3mm



Uponor Vario actuator retrofit set A-XXX 24V, NC, 1W

1083575



Technical data

| | |
|----------------------------|----------------|
| Item no EAN | 4021598131118 |
| Item no GTIN | 04021598131118 |
| Item no VVS | 466235228 |
| RSK no. | 5398304 |
| Item no NRF | 8361015 |
| Item no LVI | 2025235 |
| Item (unit of measurement) | set |
| Packaging Quantity 1 | 1 |
| Packaging Quantity 3 | 100 |
| Item Replacement 1 | 1141681 |
| Packaging GTIN PL1 | 06414905469697 |
| Packaging GTIN PL3 | 06414905453580 |
| Packaging GTIN PL4 | 0641490555185 |
| Item Unit Length | 90 |
| Item Unit Height | 42 |
| Item Unit Weight | 0,13 |
| Item Unit Width | 42 |

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb