Product data sheet

Uponor Minitec nubfoil self-adh 8pce, 6,2m2 1100x700x12mm

1083866

- Pipe fixation panel made of polystyrol, with overlap on both sides with triangular studs; perforated panel for installation between levelling compound and substructure; with self-adhesive back for proper fixture to screed and tiled floors.



About Uponor Minitec nubfoil self-adh

Specification

- Minitec underfloor heating system for fixation on solid floors or specified insulation materials
- designed as sturdy pipe fixing system of minimum height, with integrated pipe laying channels for correct pipe laying distances
- for use with Uponor Minitec PE-Xa pipes 9.9 x 1.1 mm; allowing for straight and diagonal pipe laying
- EN 13501-1 fire classification: class E.
- standard flammability, building-material class B2, conforming to DIN 4102.
- Pipe spacing: Vz 5, 10, 15
- Net surface with overlapping nubs: 0,77m²

Application

- radiant underfloor heating and cooling
- very low construction height
- for use with qualified filler materials

Certification

- DIN CERTCO: 7F170-F

Uponor Minitec nubfoil self-adh 8pce, 6,2m2 1100x700x12mm

1083866



Technical data

Item no EAN	4021598131163
Item no GTIN	04021598131163
Item no VVS	339262010
RSK no.	5363715
Item no NRF	8361056
Item no LVI	2023413
Item (unit of measurement)	set
Packaging Quantity 1	1
Packaging Quantity 4	16
Packaging GTIN PL1	06414905469819
Packaging GTIN PL4	06414905500550
Item Unit Length	1115
Item Unit Height	15
Item Unit Weight	6,16
Item Unit Width	715

Technical documents

Download documents here

Uponor UK

Blackmor Lane The Pavilion WD18 8GA, Watford UK

T +44 (0)1923 927000 E enquiries.uk@uponor.com

www.uponor.com/en-gb