

Uponor Combi Pipe white PN6 32x2,9 50m

1084387

- Operating pressure 6 bar
- Coils
- White

About Uponor Combi Pipe white PN6

Specification

- Pipes manufactured from peroxide cross-linked polyethylene (PE-Xa) acc. EN ISO 15875
- EVOH (ethylene vinyl alcohol) layer for oxygen diffusion resistance as per DIN 4726
- Application class 2 - hot water supply
- Application class 4 - Underfloor heating and low temperature radiators
- Application class 5 - high temperature radiators
- Fire classification E according to DIN EN 13501-1.

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Underfloor heating and low temperature radiators
- Heating: The permanent operating temperature ranges up to 90°C at a maximum permanent operating pressure of 6 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Uponor Combi Pipe white PN6 32x2,9 50m

1084387

Technical data

Item no EAN	6414905514496
Item no GTIN	06414905514496
Item (unit of measurement)	m
Packaging Quantity 1	50
Packaging Quantity 4	300
Item Replacement 1	1038365
Packaging GTIN PL1	06414905417087
Packaging GTIN PL4	06414905430505
Item Unit Length	1000
Item Unit Height	32
Item Unit Weight	0,289
Item Unit Width	32

Technical documents

[Download documents here](#) 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb