

Uponor Vario S regulation valve ST

1084785



About Uponor Vario S regulation valve ST

Specification

- Made of stainless steel
- With integrated valves
- Connection right or left with flat sealing
- Integrated airvents and fill&drain points in supply and return,
- Loop connection G3/4" eurocone
- Loop pitch 50 mm
- Header pitch 215 mm

Application

- For underfloor-heating and -cooling
- Applicable with actuators 1141676 (230V) and 1141677 (24V)
- Max. pressure: 6 bar at 60°C

Uponor Vario S regulation valve ST

1084785



Technical data

Item no EAN	4021598132665
Item no GTIN	04021598132665
Item (unit of measurement)	pce
Packaging Quantity 1	1
Packaging Quantity 3	50
Packaging Material short PL1	LDPE
Packaging Material short PL3	PAP
Packaging Material PL1	Low density polyethylene
Packaging Material PL3	Corrugated fibreboard
Packaging GTIN PL1	06414905470372
Packaging GTIN PL3	06414905453825
Item Unit Length	26
Item Unit Height	53
Item Unit Weight	0,068
Item Unit Width	26

Technical documents

Download documents here

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb