

Uponor Vario S actuator 24 V 1 W NC FT 30x1,5

1087778

- useable for manifolds with the connection FT 30x1,5
- incl. 1 bayonet manifold valve adaptor ring M30x1.5mm and mounting instructions
- first open function
- Autobalancing functionality for new and retrofit installations
- manifold adaptor: M30x1.5mm
- height: 58mm + adaptor ring
- stroke length: 5mm
- connection cable: 2x 0.75mm²x1m
- diameter: 44.3mm
- conformity: EAC
- color: blue
- compatible to Uponor Smatrix controller
- 24V
- Ucoil: 24V/50Hz



About Uponor Vario S actuator 24 V 1 W NC

Specification

- Made of stainless steel
- With integrated valves
- Connection right or left with flat sealing
- Integrated airvents and fill&drain points in supply and return,
- Loop connection G3/4" eurocone
- Loop pitch 50 mm
- Header pitch 215 mm

Application

- For underfloor-heating and -cooling
- Applicable with actuators 1141676 (230V) and 1141677 (24V)
- Max. pressure: 6 bar at 60°C

Uponor Vario S actuator 24 V 1 W NC FT 30x1,5

1087778



Technical data

Item no EAN	4021598149786
Item no GTIN	04021598149786
Item no VVS	466235324
Item no LVI	2024552
Item (unit of measurement)	set
Packaging Quantity 1	1
Packaging Quantity 4	100
Packaging Quantity 4	2000
Item Replacement 1	1141677
Packaging GTIN PL1	06414905440818
Packaging GTIN PL2	06414905443000
Packaging GTIN PL4	0641490555215
Item Unit Length	48
Item Unit Height	52
Item Unit Weight	0,14
Item Unit Width	44

Technical documents

Download documents here

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb