

Uponor Vario PLUS actuator PRO 230v 1W NC VA02 MT 30x1,5

1090263

- interface between existing third-party manifolds and Uponor
- open/closed indicator
- first open function
- temperature range: 0°C ... +60°C
- height: 58mm + adaptor ring
- stroke length: 5mm
- connection cable: 2x 0.75mm²x1m
- diameter: 44.3mm
- conformity: EAC
- protection class: IP54
- color: blue

Consisting of:

- Vario PLUS actuator
- bayonet manifold valve adaptor ring M30x1.5mm
- mounting instructions



About Uponor Vario PLUS actuator PRO 230v 1W NC

Specification

- Modular fibre glass reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- connection right or left with flat sealing or connection from below with optional elbowset
- supply with lockshield (LS) valve for balancing with adjusting ring or supply with Flowmeter (FM) for balancing
- shut-off and flow view
- adjusting ring for balancing without tools
- prepared places for room name labels
- return with valves and caps, prepared for actuators
- loop connection G3/4" eurocone
- loop pitch 50 mm
- header pitch 225 mm

Actuator:

- NC (normally closed) = closes without power

Application

- for underfloor heating and cooling
- combineable with actuators MT 30x1,5

Certification

- CE

Uponor Vario PLUS actuator PRO 230v 1W NC VA02 MT 30x1,5

1090263



Technical data

Item no EAN	6414905217946
Item no GTIN	06414905217946
Item no VVS	466235126
RSK no.	2987937
Item no NRF	8361106
Item no LVI	2024325
Item (unit of measurement)	pce
Packaging Quantity 1	1
Packaging Quantity 4	100
Packaging Quantity 4	2000
Item Replacement 1	1141678
Packaging GTIN PL1	06414905441259
Packaging GTIN PL2	06414905443215
Packaging GTIN PL4	0641490555222
Item Unit Length	40
Item Unit Height	58
Item Unit Weight	0,1
Item Unit Width	85

Technical documents

Download documents here

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb