

Uponor Vario B actuator PRO 24V 1W NC VA32 FT 28x1,5

1090264

- incl. 1 bayonet manifold valve adaptor ring M28x1.5mm and mounting instructions
- first open function
- Autobalancing functionality for new and retrofit installations
- manifold adaptor: M28x1.5mm
- height: 58mm + adaptor ring
- stroke length: 5mm
- connection cable: 2x 0.75mm²x1m
- diameter: 44.3mm
- conformity: EAC
- color: blue
- compatible to Uponor Smatrix controller



About Uponor Vario B actuator PRO 24V 1W NC

Specification

- Made of brass
- With integrated valves
- Connection right or left with flat sealing supply
- With lockshield valve or flowmeter for balancing and shutoff
- no primary connection to combine it with the correct accessories
- Loop connection G3/4" eurocone
- Loop distance 50 mm
- Bracket distance 210 mm

Application

- For underfloor heating and cooling
- Combineable with actuators FT 30x1,5
- Max. pressure: 6 bar at 60°C

Uponor Vario B actuator PRO 24V 1W NC VA32 FT 28x1,5

1090264



Technical data

Item no EAN	6414905217953
Item no GTIN	06414905217953
Item no VVS	466235024
RSK no.	2987938
Item no NRF	8361107
Item no LVI	2024326
Item (unit of measurement)	pce
Packaging Quantity 1	1
Packaging Quantity 4	100
Packaging Quantity 4	2000
Item Replacement 1	1141681
Packaging GTIN PL1	06414905441266
Packaging GTIN PL2	06414905443222
Packaging GTIN PL4	0641490555246
Item Unit Length	40
Item Unit Height	58
Item Unit Weight	0,1
Item Unit Width	85

Technical documents

Download documents here

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb