Uponor Combi Port M-Base HeatInterface RC 15 CB TL ZV NI

1093802

RC version for domestic hot water and direct heating with radiator connection (no mixing circuit). Mixing circuit can be upgraded by using the dedicated cabinet with installed UFH mixing group (Uponor Combi Port M-Base Cabinet+manif IW-UFH). Bypass function can be upgraded by using special accessory - Uponor Combi Port M-Base Heat Bypass.

Dimensioning codes:

15,19 - domestic hot water capacity indication (I/min)


CB - copper brazed stainless steel heat exchanger for domestic hot water preparation


TL – thermostatic temperature limiter for domestic hot water with submersible sensor

ZV - zone valve in residential heating circuit return line without actuator

NI - no pipe insulation and/or insulated cover









About Uponor Combi Port M-Base HeatInterface RC

Specification

- port completely assembled and pressure tested
- pipe clamps made of plastic for sound protection and thermal decoupling
- DVGW certified PM Valve with patented triple-sealing technology
- cold water outlet
- spacer for heat meter 110 mm x3/4"
- spacer for water meter 110 mm x3/4"
- venting and drainage valve
- strainer for primary heating supply line 0,5 mm
- connection possibility (marked) of an electrical earthing lug
- max. operating pressure heating: PN10
- max. operating pressure sanitary: PN10
- max. operating temperature: 85 °C
- min. pressure sanitary: 2,0 bar
- fitting material sanitary: CW617N
- fitting material heating: CW617N, CW614N
- pipe material: stainless steel 1.4401
- measurements: W/H/D 556 x 620 x 110 mm

Application

- Decentralized instantaneous domestic hot water generation
- Underfloor heating systems
- Radiator heating systems


Certification


- DVGW approval

Uponor Combi Port M-Base HeatInterface RC 15 CB TL ZV NI

1093802







Technical data

Item no EAN	6414905231324
Item no GTIN	06414905231324
Item (unit of measurement)	pce
Length (I)	556 mm
Length (I1)	83 mm
Z-measurement b	65 mm
Z-measurement h	107 mm
Z-measurement h1	35 mm
Z-measurement w	618 mm
Z-measurement w1	600 mm
Packaging Quantity 1	1
Packaging Quantity 4	16
Packaging GTIN PL1	06414905292592
Packaging GTIN PL4	06414905293193
Item Unit Length	600
Item Unit Height	110
Item Unit Weight	12,4
Item Unit Width	555

Technical documents

Download documents here

Oponioi On

Blackmor Lane The Pavilion WD18 8GA, Watford

T +44 (0)1923 927000 E enquiries.uk@uponor.com

www.uponor.com/en-gb