
Uponor Combi Port M-Pro Cabinet IW 840x610x110mm

1093809

In-wall mounted cabinet including feet







About Uponor Combi Port M-Pro Cabinet IW

Specification

- port completely assembled and pressure tested
- technical limits of use in water for heating and plumbing are shown in technical data sheets
- pipe clamps made of plastic for sound protection and thermal decoupling
- DVGW certified PM Valve with patented triple-sealing technology
- thermal insulation at the supply pipes
- thermostatic bypass valve
- cold water outlet
- spacer for heat meter 110 mm x3/4"
- spacer for water meter 110 mm x3/4"
- venting and drainage valve
- strainer for cold water 0,5 mm
- strainer for primary heating supply line 0,5 mm
- Connection possibility (marked) of an electrical earthing lug
- max. operating pressure heating: PN10
- max. operating pressure sanitary: PN10
- max. operating temperature: 85 °C
- max. differential pressure primary heating: 2,5 bar
- min. pressure sanitary: 2,0 bar
- fitting material sanitary: CW617N
- fitting material heating: CW617N, CW614N
- pipe material: stainless steel 1.4401
- measurements: W/H/D 556 x 620 x 110 mm

Application

- Decentralized instantaneous domestic hot water generation
- Underfloor heating systems
- Radiator heating systems

Certification


- DVGW approval

Uponor Combi Port M-Pro Cabinet IW 840x610x110mm

1093809







Technical data

Item no EAN	6414905231393
Item no GTIN	06414905231393
Item (unit of measurement)	pce
Length (I)	655 mm
Length (I1)	610 mm
Z-measurement b	839 mm
Z-measurement b1	23 mm
Z-measurement h	110 mm
Z-measurement h1	135 mm
Z-measurement w	1090 mm
Z-measurement w1	840 mm
Packaging Quantity 1	1
Packaging Quantity 4	8
Packaging GTIN PL1	06414905292684
Packaging GTIN PL4	06414905293292
Item Unit Length	840
Item Unit Height	110
Item Unit Weight	15
Item Unit Width	610

Technical documents



Blackmor Lane The Pavilion WD18 8GA, Watford UK

T +44 (0)1923 927000 E enquiries.uk@uponor.com

www.uponor.com/en-gb