## Uponor Combi Port M-Pro Cabinet+manif IW 1200x750X110mm 8HM+9BV


## 1093817

In-wall mounted cabinet including feet, heating manifold, and rail with pre-installed ball valves. Not needed circuits need to be plugged on site. Dimensioning codes:

HMV - set of Vario-S manifolds for heating with \_ (4,6,8,10) heating circuits

BV - set of 9 ball valves pre-installed on the mounting rail inside the cabinet for heat interface connections





### About Uponor Combi Port M-Pro Cabinet+manif IW

#### Specification

- port completely assembled and pressure tested
- technical limits of use in water for heating and plumbing are shown in technical data sheets
- pipe clamps made of plastic for sound protection and thermal decoupling
- DVGW certified PM Valve with patented triple-sealing technology
- thermal insulation at the supply pipes
- thermostatic bypass valve
- cold water outlet
- spacer for heat meter 110 mm x3/4"
- spacer for water meter 110 mm x3/4"
- venting and drainage valve
- strainer for cold water 0,5 mm
- strainer for primary heating supply line 0,5 mm
- Connection possibility (marked) of an electrical earthing lug
- max. operating pressure heating: PN10
- max. operating pressure sanitary: PN10
- max. operating temperature: 85 °C
- max. differential pressure primary heating: 2,5 bar
- min. pressure sanitary: 2,0 bar
- fitting material sanitary: CW617N
- fitting material heating: CW617N, CW614N
- pipe material: stainless steel 1.4401
- measurements: W/H/D 556 x 620 x 110 mm

#### Application

- Decentralized instantaneous domestic hot water generation
- Underfloor heating systems
- Radiator heating systems


#### Certification

- DVGW approval

# Uponor Combi Port M-Pro Cabinet+manif IW 1200x750X110mm 8HM+9BV 1093817

N III III III III III III III III III I	~
and the second se	
the second se	119
the second se	1111
the second se	
the second se	114
	114
2	18
0.54	
	. ни
	2
22 2 2 2 2 2 2 2 2 2 2	1161
- with filling (	
88885	
The state of the s	
A A A A A A A A A A A A A A A A A A A	1100
Call of the second s	114
(Changapper)	trac
( CONTRACTOR )	
(Channahana)	





#### **Technical data**

Item no EAN	6414905231478
Item no GTIN	06414905231478
Item (unit of measurement)	pce
Length (I)	795 mm
Length (I1)	750 mm
Z-measurement b	1190 mm
Z-measurement b1	23 mm
Z-measurement h	110 mm
Z-measurement h1	135 mm
Z-measurement w	1440 mm
Z-measurement w1	1190 mm
Packaging Quantity 1	1
Packaging Quantity 4	8
Packaging GTIN PL1	06414905292493
Packaging GTIN PL4	06414905293094
Item Unit Length	1200
Item Unit Height	110
Item Unit Weight	20
Item Unit Width	750

#### **Technical documents**

Download documents here

Blackmor Lane The Pavilion WD18 8GA, Watford UK

T +44 (0)1923 927000 E enquiries.uk@uponor.com

www.uponor.com/en-gb