



## Uponor Ecoflex weldable adapter ST PN6 EU 50x4,6-48,3

**1094016**

- Connection of PE-Xa pipes
- 6 bar, SDR 11
- Steel adapter for welding



### About Uponor Ecoflex weldable adapter ST PN6

#### Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

#### Application



- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

#### Certification

- Approvals should be checked by local responsible person

## Uponor Ecoflex weldable adapter ST PN6 EU 50x4,6-48,3

1094016



### Technical data

Item no EAN	6414905231744
Item no GTIN	06414905231744
Item (unit of measurement)	pce
Length (l)	84 mm
Length (l1)	36 mm
Z-measurement d	NaN mm
Packaging Quantity 1	1
Packaging GTIN PL1	06414905278336
Item Unit Length	84
Item Unit Height	72
Item Unit Weight	0,7000
Item Unit Width	84

### Technical documents

[Download documents here](#)

#### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)