



Uponor Ecoflex weldable adapter ST PN6 EU+GOST 75x6,8-76,1

1094018

- Connection of PE-Xa pipes
- 6 bar, SDR 11
- Steel adapter for welding



About Uponor Ecoflex weldable adapter ST PN6

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application



- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Ecoflex weldable adapter ST PN6 EU+GOST 75x6,8-76,1

1094018



Technical data

Item no EAN	6414905231768
Item no GTIN	06414905231768
Item (unit of measurement)	pce
Length (l)	101 mm
Length (l1)	53 mm
Z-measurement d	NaN mm
Packaging Quantity 1	1
Packaging GTIN PL1	06414905278350
Item Unit Length	101
Item Unit Height	106
Item Unit Weight	1,6
Item Unit Width	116

Technical documents

Download documents here

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb