



## Uponor Ecoflex weldable adapter ST PN6 EU+GOST 125x11,4-114,3

**1094021**

- Connection of PE-Xa pipes
- 6 bar, SDR 11
- Steel adapter for welding



### About Uponor Ecoflex weldable adapter ST PN6

#### Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

#### Application



- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

#### Certification

- Approvals should be checked by local responsible person

## Uponor Ecoflex weldable adapter ST PN6 EU+GOST 125x11,4-114,3

1094021



### Technical data

Item no EAN	6414905231799
Item no GTIN	06414905231799
Item (unit of measurement)	pce
Length (l)	119 mm
Length (l1)	69 mm
Z-measurement d	NaN mm
Packaging Quantity 1	1
Packaging GTIN PL1	06414905278381
Item Unit Length	119
Item Unit Height	163
Item Unit Weight	4,4
Item Unit Width	180

### Technical documents

Download documents here

#### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E enquiries.uk@uponor.com

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)