

## Uponor Combi Port M-ProX HeatInterface IH 15 CB BP DI TL ZH CR NI NC

**1095636**

IH version for domestic hot water and indirect heating systems using second heat exchanger with heating circuit connections including heating pump and expansion tank mounted on the side of heat interface unit.

Dimensioning codes:

15, 21 – domestic hot water capacity indication (l/min)

CB – copper brazed stainless steel heat exchanger for domestic hot water preparation

BP – supply lines preheating function

DI – primary differential pressure controller at the heat interface unit inlet


TL – thermostatic temperature limiter for domestic hot water with submersible sensor

ZH – apartment heating circuit circulation arrangement, including circulation pump, thermostatic flow controller and expansion tank


CR – heat interface metal cover casing white powder coated (RAL 9016)

NI – no pipe insulation and/or insulated cover

NC – no cold water outlet from heat interface unit



## Uponor Combi Port M-ProX HeatInterface IH 15 CB BP DI TL ZH CR NI NC 1095636



### Technical data

Item no EAN	6414905478330
Item no GTIN	06414905478330
Item (unit of measurement)	pce
Length (l)	436 mm
Length (l1)	68 mm
Length (l2)	168 mm
Length (l3)	30 mm
Z-measurement b	50 mm
Z-measurement h	251 mm
Z-measurement h1	39 mm
Z-measurement w	747 mm
Z-measurement w1	648 mm
Packaging Quantity 1	1
Packaging GTIN PL1	06414905486786
Packaging GTIN PL4	06414905486793
Item Unit Length	600
Item Unit Height	282
Item Unit Weight	35
Item Unit Width	470

#### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)