

Uponor Ecoflex Thermo connection set twin hp 2x32x2,9-2x32x3,5/140

L=12m

1105779

- A to B connection set include
- Ecoflex Thermo Twin HP heating pipe
- 2 pieces of Quattro rubber end caps
- 4 pieces of Couplings
- 30m of Trench warning tape
- box size in table = w,b,h



About Uponor Ecoflex Thermo connection set twin hp

Specification

- Flexible, pre-insulated, self-compensating plastic pipe system produced based on EN 15632
- Medium pipe: cross-linked polyethylene (PE-Xa) pipe based on EN ISO 15875, natural coloured, PN 6 (SDR 11) or PN 10 (SDR 7,4), Oxygen tightness based on EN 15632
- Insulating material: closed-cell PE-X foam, permanently elastic, ageing-resistant
- Casing pipe: Corrugated polyethylene (HDPE)

Application

- Transport of heating and cooling water for buried installations.
- Heating operating temperature 80°C based on EN 15632
- Malfunction temperature 95°C
- Static verification for heavy traffic load of 60 tons

Certification

- Approvals should be checked by local responsible person

Uponor Ecoflex Thermo connection set twin hp 2x32x2,9-2x32x3,5/140

L=12m

1105779



Technical data

Item no EAN	6414905528776
Item no GTIN	06414905528776
Item no VVS	087808852
Item (unit of measurement)	set
Packaging Quantity 1	1
Packaging Quantity 4	4
Packaging GTIN PL1	06414905542833
Packaging GTIN PL4	06414905542840
Item Unit Length	1550
Item Unit Height	1550
Item Unit Weight	29,42
Item Unit Width	300

Technical documents

Download documents here

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb