

## Uponor Ecoflex Supra PLUS con. and end set 40+50+63/140

1120126

- Connection and end set for Supra PLUS pipe
- Unit controls max.150m frost protection cable
- Controller with 10m sensor cable
- Set 1 electrical parts for supply cable - frost protection cable joint and cable end termination
- Two rubber end caps



### About Uponor Ecoflex Supra PLUS con. and end set

#### Specification

- Flexible, pre-insulated, self-compensating plastic pipe system
- Medium pipe: Polyethylene PE80, PN 12,5 (SDR 11) or PE100, PN 16 (SDR 11) black with blue stripes or PE 100, PN 16 (SDR 11) black with blue layer and new in PE100 RC, PN16 (SDR11) black with blue stripes
- Cable: self-regulating frost protection cable, nominal power output 10W/m at 5°C, Electricity feed from one supply point max. 150 m
- Conduit pipe: PE tube to insert a sensor and to measure the temperature.
- Insulating material: closed-cell PE-X foam, permanently elastic, ageing-resistant
- Casing pipe: Corrugated polyethylene (HDPE)

#### Application

- Transport of cold potable water or pressure drainage in locations where there is a risk of freezing for buried installations.
- Operating temperature +20°C
- Static verification for heavy traffic load of 60 tons

#### Certification

- Approvals should be checked by local responsible person

## Uponor Ecoflex Supra PLUS con. and end set 40+50+63/140

1120126



### Technical data

Item no EAN	6414905633210
Item no GTIN	06414905633210
Item no VVS	070699863
RSK no.	2407843
Item no NRF	8360725
Item no LVI	1844028
Item (unit of measurement)	set
Packaging Quantity 1	1
Packaging GTIN PL1	06414905641116
Item Unit Length	380
Item Unit Height	140
Item Unit Weight	1,197
Item Unit Width	280

### Technical documents

Download documents here

#### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)