

Uponor Aqua Ambient point drain inlet c standard FI 50

1136458

- connection to sewage pipes DN 50 or DN 110
- flow rate: DN 50 0,8 l/s, DN 110 1,4 l/s
- material grate: stainless steel
- material body: polypropylene

About Uponor Aqua Ambient point drain inlet c standard

Specification

- Modern construction and stylish design in different sizes: 600, 700, 800, 900, 1000mm
- Wide sealing collar (30mm) ensuring tight jointing to the floor construction
- Adjustable height and fixable legs for integration in every kind of floor construction
- Easy installation due to product completeness and compatibility to wastewater installation system (dimension of waste pipes)
- 360° tunable siphon

Application

- Housing sewage systems

Certification

- Technical assessment acc EN 1253

Uponor Aqua Ambient point drain inlet c standard FI 50

1136458

Technical data

Item no EAN	6414900483551
Item no GTIN	06414900483551
Item (unit of measurement)	pce
Length (l1)	107 mm
z	100 mm
Z-measurement h	124 mm
Z-measurement h1	83 mm
Z-measurement h2	40 mm
Packaging Quantity 1	1
Packaging Quantity 4	180
Packaging GTIN PL1	06414900369459
Packaging GTIN PL4	06414900370097
Item Unit Length	210
Item Unit Height	149
Item Unit Weight	0,35
Item Unit Width	210

Technical documents

[Download documents here](#) 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb