

Uponor Aqua Ambient point drain inlet pass super/spot FI 50

1136466

- connection to sewage pipes DN 50
- flow rate: 0,4 l/s
- for low floor constructions
- material grate: stainless steel
- material body: polypropylene

About Uponor Aqua Ambient point drain inlet pass super/spot

Specification

- Modern construction and stylish design in different sizes: 600, 700, 800, 900, 1000mm
- Wide sealing collar (30mm) ensuring tight jointing to the floor construction
- Adjustable height and fixable legs for integration in every kind of floor construction
- Easy installation due to product completeness and compatibility to wastewater installation system (dimension of waste pipes)
- 360° tunable siphon

Application

- Housing sewage systems

Certification

- Technical assessment acc EN 1253

Uponor Aqua Ambient point drain inlet pass super/spot FI 50

1136466

Technical data

Item no EAN	6414900483650
Item no GTIN	06414900483650
Item (unit of measurement)	pce
Length (l1)	120 mm
Z-measurement h	55 mm
Z-measurement h1	38 mm
Z-measurement h2	38 mm
Packaging Quantity 1	1
Packaging Quantity 4	300
Packaging GTIN PL1	06414900369398
Packaging GTIN PL4	06414900370141
Item Unit Length	220
Item Unit Height	80
Item Unit Weight	0,4
Item Unit Width	220

Technical documents

[Download documents here](#) 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb