

EP heating manifold isolation valve bodies

Project information

| | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Date submitted: |
| Contractor: | Submitted by: |
| Manufacturer's representative: | Approved by: |

Technical data

| | |
|---------------------------------|---|
| Subcomponent Material | Manifold: PA66-GF30 Valve Insert, Handwheels: POM Metal Inserts: Brass C38500 Axel: Stainless Steel Spring: Stainless Steel O-ring: EPDM |
| Loop Cv | 1.4 Cv |
| End type 1 | ISO 228-G 3/4" |
| Temp/pressure ratings | 140 °F (60 °C) at 87 psi (6 bar) 158 °F (70 °C) at 72 psi (5 bar) 176 °F (80 °C) at 58 psi (4 bar) 194 °F (90 °C) at 44 psi (3 bar) |
| Operating temperature min. [°F] | 44.6 °f |
| Max. fluid flow rate | 15.4 gpm |
| Prop 65 label required? | Yes |



Product information and application use

(Replacement part) Uponor EP heating manifold isolation valve bodies replace the isolation valve on the return manifold.

| Part name | Part no. | Weight per UOM [lbs/UOM] |
|--|----------|--------------------------|
| EP Heating Manifold Isolation Valve Body, replacement part | A2670004 | 0.05 |

Installation

N/A

Related applications

Radiant heating systems

Notes

Adaptable Actuators:

EP Heating Manifold, two-wire Actuator (A3030522); Thermal Actuator, four-wire (A3010522) with EP Heating Manifold Actuator Adaptor (A2671300)

Connection Dimensions: R32

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517