


ProPEX lead-free (LF) brass water meter valves

Project information

| | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Date submitted: |
| Contractor: | Submitted by: |
| Manufacturer's representative: | Approved by: |

Technical data

| | |
|-------------------------|--|
| Material | LF Brass |
| Subcomponent Material | Valve: C27453 lead-free (LF) brass per ASTM B283/B283M Metal nut: UNS CW614 per ASTM B16/B16M EP nut: Polypropylene GF30 black Gasket: EPDM |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar) |
| Prop 65 label required? | Yes |



Product information and application use

Use Uponor ProPEX® lead-free (LF) brass water meter service valves in all commercial submetering and residential water service inlets, outlets or both. The valves allow for a direct ASTM F1960 connection to water meters sized 5/8" to 1". Valve is sized for 3/4" or 1" Uponor AquaPEX® tubing. Product handle material is stainless steel.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.

| Part name | Part no. | A [Inch] | B [Inch] | C [Inch] | D [Inch] | E [Inch] | F [Inch] | G [Inch] | H [Inch] | I [Inch] | J [Inch] |
|--|-----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|
| ProPEX LF Brass Straight Water Meter Valve, 3/4" PEX x 1" NPSM | WS4820750 | 0.945 | 2.957 | 1.551 | 2.992 | 0.591 | 1.9 | 1.299 | 4.278 | 2.501 | 5.734 |
| ProPEX LF Brass Straight Water Meter Valve, 1" PEX x 1 1/4" NPSM | WS4821000 | 1.181 | 3.302 | 2.015 | 3.819 | 0.677 | 2.25 | 1.614 | 5.158 | 3.139 | 7.119 |
| ProPEX LF Brass Elbow Water Meter Valve, 3/4" PEX x 1" NPSM | WS4820751 | 0.945 | 2.249 | 1.551 | 2.992 | 0.781 | 1.9 | 1.299 | 0.65 | 3.277 | 5.735 |
| ProPEX LF Brass Elbow Water Meter Valve, 1" PEX x 1 1/4" NPSM | WS4821001 | 1.181 | 2.625 | 2.015 | 3.819 | 0.827 | 2.25 | 1.614 | 0.807 | 4.022 | 7.119 |

| Part name | Part no. | K [Inch] | Cv | End Type 1 | End Type 2 | Operating temperature min. [°F] | Weight per UOM [lbs/UOM] |
|--|-----------|----------|------|-------------|-------------|---------------------------------|--------------------------|
| ProPEX LF Brass Straight Water Meter Valve, 3/4" PEX x 1" NPSM | WS4820750 | 0.65 | 10.9 | ProPEX 3/4" | NPSM 1" | - | 0.76 |
| ProPEX LF Brass Straight Water Meter Valve, 1" PEX x 1 1/4" NPSM | WS4821000 | 0.807 | 18.7 | ProPEX 1" | NPSM 1-1/4" | -29 | 1.22 |
| ProPEX LF Brass Elbow Water Meter Valve, 3/4" PEX x 1" NPSM | WS4820751 | 0.65 | 4.9 | ProPEX 3/4" | NPSM 1" | -29 | 0.76 |
| ProPEX LF Brass Elbow Water Meter Valve, 1" PEX x 1 1/4" NPSM | WS4821001 | 0.807 | 9.7 | ProPEX 1" | NPSM 1-1/4" | - | 1.24 |

| Part name | Part no. | Codes | Standards | Listings |
|--|----------|--|---|----------------------------------|
| ProPEX lead-free (LF) brass water meter valves | All | UPC IBC IRC IPC NPC of Canada UMC NSPC IMC | ASTM F877 NSF/ANSI/CAN 372 NSF/ANSI 359 ASTM F1960 CSA B137.5 NSF/ANSI/CAN 61 NSF/ANSI 14 | HUD MR 1269 cNSFus-pw-G U.P.Code |

In addition, the following parts have additional codes, standards, or listings:

| | |
|---|-----------|
| ProPEX LF Brass Elbow Water Meter Valve, 1" PEX x 1 1/4" NPSM | WS4821001 |
|---|-----------|

Installation

ProPEX tool and ProPEX rings (sold separately) are required for connecting the PEX tubing. For more information, refer to the Uponor Residential Plumbing Systems Installation Guide or the Uponor Piping Systems Installation Guide.

Related applications

PEX-a Plumbing Systems

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517
