

Uponor PP-RCT 90 street elbows (socket fusion)

Project information	
Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:


Technical data

PP-RCT Material

Temp/pressure ratings 73 °F (23 °C) at 340 psi (23.44 bar) 140 °F (60 °C) at 190 psi (13.1 bar) 180 °F (82 °C) at 100 psi (6.9 bar)

Product information and application use

Use Uponor PP-RCT Socket-Fusion 90 Street Elbows with Uponor PP-RCT Mechanical Pipe to convey fluid for hydronic heating and cooling or industrial applications and with Uponor PP-RCT Potable Pipe to convey water for potable plumbing applications.



Part name	Part no.	A [inch]	B [inch]	C [inch]	D [inch]	E [inch]	F [inch]	G [inch]	H [inch]	Equivalent length through [ft]	End Type 1
Uponor PP-RCT 90 Street Elbow, 1" x 1	PR4439010	0.713	0.496	0.825	0.575	2.033	2.224	1.65	0.825	2.6	Socket 1"
Uponor PP-RCT 90 Street Elbow, 1/2" x 1/2	PR4439050	0.63	0.374	0.728	0.61	1.598	1.933	1.189	0.594	1.6	Socket 1/2"
Uponor PP-RCT 90 Street Elbow, 3/4" x 3/4	PR4439075	0.63	0.366	0.642	0.492	1.638	1.776	1.283	0.642	2	Socket 3/4"

Part name	Part no.	End Type 2	Weight per UOM [lbs/UOM]
Uponor PP-RCT 90 Street Elbow, 1" x 1	PR4439010	Socket 1"	0.1
Uponor PP-RCT 90 Street Elbow, 1/2" x 1/2	PR4439050	Socket 1/2"	0.05
Uponor PP-RCT 90 Street Elbow, 3/4" x 3/4	PR4439075	Socket 3/4"	0.05

Part name	Part no.	Codes	Standards	Listings
Uponor PP-RCT 90 street elbows (socket fusion)	All	CMC IMC UMC	NSF/ANSI/CAN 61 ASTM E84 NSF/ANSI 14 ASTM F2389 CSA B137.11	ICC-ES-PMG 1106 IAPMO-R&T 8358 QAI P321-5 IAPMO K-12775

Installation Related applications

Use approved socket-fusion connection methods. Refer to the Uponor PP-RCT manual for complete

Hydronic heating and cooling systems

Industrial

Domestic water systems

Footnotes	Contact i	Contact information		
	Uponor Inc.	Uponor Ltd.		
	5925 148th Street West	6510 Kennedy Road		
-	Apple Valley, MN 55124	Mississauga, ON L5T 2X4		
	T 800.321.4739	T 888.594.7726		
	F 952 891 2008	F 800 638 9517		