

# EP heating manifold elbows

## Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

## Technical data

Temp/pressure ratings	140 °F (60 °C) at 87 psi (6 bar)
	158 °F (70 °C) at 72 psi (5 bar)
	176 °F (80 °C) at 58 psi (4 bar)
	194 °F (90 °C) at 44 psi (3 bar)
Prop 65 label required?	Yes

## Product information and application use

The Engineered Polymer (EP) Heating Manifold Elbow (A2670090) enables connections to supply and return piping from above or below. Two elbows feature different lengths to accommodate tube spacing for the supply and return lines on a EP Heating Manifold for use in hydronic radiant heating and cooling systems. Use only propylene glycol in radiant systems with EP Heating Manifolds; never use ethylene glycol.



Part name	Part no.	Weight per UOM [lbs/UOM]
EP Heating Manifold Elbow, set of 2	A2670090	0.34

## Installation

Hand-tighten the elbow to the supply and return on the manifold. For additional information, refer to the instruction sheet. Note: Use only propylene glycol in radiant heating and cooling systems with EP Heating Manifolds; never use ethylene glycol. Refer to the EP Heating Manifold Installation Guide for a complete chemicals list.

## Related applications

Radiant Heating and Cooling Systems  
 Permafrost Protection Systems  
 Turf Conditioning Systems

## Footnotes

-

## Contact information

Uponor Inc.  
 5925 148th Street West  
 Apple Valley, MN 55124  
 T 800.321.4739  
 F 952.891.2008

Uponor Ltd.  
 6510 Kennedy Road  
 Mississauga, ON L5T 2X4  
 T 888.594.7726  
 F 800.638.9517