

Xpress Trak

Project Information


Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material	Aluminum Laminate w/XPS Foam
Operating temperature min. [°F]	50 °f
Operating temperature max. [°F]	150 °f
R value	3.13
Prop 65 label required?	Yes

Product information and application use

Designed for residential new construction and remodels, Xpress Trak™ is a radiant panel that features lightweight XPS foam laminated with aluminum for exceptional heat-transfer capability. Straight runs and return bends are integrated into one panel for quick, easy ordering. To install, simply adhere the panels to a wood subfloor or a concrete slab.



Part name	Part no.	A [inch]	B [inch]	C [inch]	D [inch]	E [inch]	F [inch]	G [inch]	Weight per UOM [lbs/UOM]
Xpress Trak Radiant Panel, 6" o.c., 4 runs	A5070641	23.622	47.244	0.63	2.953	5.906	1.488	1.457	1.45

Installation

Use water-based sealant to adhere the panels to a wood subfloor or a concrete slab. Then, press the 5/16" Wirsbo hePEX™ pipe into the panel grooves using hands or feet. For further information, refer to the Xpress Trak Installation Guide.

Related applications

Radiant heating

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517