

ChlorFIT Fitting Coupling Reducing

Project Information

| | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Date submitted: |
| Contractor: | Submitted by: |
| Manufacturer's representative: | Approved by: |

Technical data

Material CPVC

Product information and application use

Use Uponor ChlorFIT® Schedule 80 Corzan® CPVC Couplings in hot and cold potable-water systems as well as hydronic heating and cooling applications.



| Part name | Part no. | A [Inch] | B [Inch] | C [Inch] | D [Inch] | E [Inch] | F [Inch] | G [Inch] | H [Inch] | I [Inch] | End Type 1 |
|---|-----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|---------------|
| 3/4" x 1/2" CPVC 80 Reducing Coupling (SxS) | 9829101 | 1.047 | 0.11 | 0.922 | 2.079 | 0.755 | 1.51 | 0.64 | 1.28 | 0.28 | Socket 3/4" |
| 1" x 1/2" CPVC 80 Reducing Coupling (SxS) | 9829130 | 1.188 | 0.1 | 0.922 | 2.21 | 0.925 | 1.85 | 0.64 | 1.28 | 0.28 | Socket 1" |
| 1" x 3/4" CPVC 80 Reducing Coupling (SxS) | 9829131 | 1.134 | 0.117 | 1.009 | 2.26 | 0.928 | 1.857 | 0.763 | 1.526 | 0.41 | Socket 1" |
| 1-1/4" x 3/4" CPVC 80 Reducing Coupling (SxS), Bushed | 9829167FB | 1.272 | 0.686 | 1.012 | 2.97 | 1.044 | 2.088 | 1.09 | 2.18 | 0.82 | Socket 1-1/4" |
| 1-1/4" x 1" CPVC 80 Reducing Coupling (SxS), Bushed | 9829168FB | 1.272 | 0.567 | 1.148 | 2.987 | 1.044 | 2.088 | 1.089 | 2.178 | 0.525 | Socket 1-1/4" |
| 1-1/2" x 1/2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829209FB | 1.394 | 0.108 | 1.151 | 2.654 | 1.302 | 2.603 | 0.928 | 1.855 | 0.526 | Socket 1-1/2" |
| 1-1/2" x 3/4" CPVC 80 Reducing Coupling (SxS), Bushed | 9829210FB | 1.394 | 0.52 | 1.022 | 2.937 | 1.302 | 2.603 | 0.928 | 1.855 | 0.411 | Socket 1-1/2" |
| 1-1/2" x 1" CPVC 80 Reducing Coupling (SxS) | 9829211 | 1.438 | 0.124 | 1.188 | 2.75 | 1.25 | 2.5 | 0.925 | 1.85 | 0.525 | Socket 1-1/2" |
| 1-1/2" x 1-1/4" CPVC 80 Reducing Coupling (SxS) | 9829212 | 1.438 | 0.1 | 1.312 | 2.85 | 1.25 | 2.5 | 1.065 | 2.13 | 0.645 | Socket 1-1/2" |
| 2" x 1/2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829247FB | 1.69 | 0.316 | 1.147 | 3.153 | 1.587 | 3.174 | 0.881 | 1.762 | 0.554 | Socket 2" |
| 2" x 3/4" CPVC 80 Reducing Coupling (SxS), Bushed | 9829248FB | 1.69 | 0.316 | 1.147 | 3.153 | 1.587 | 3.174 | 0.881 | 1.762 | 0.554 | Socket 2" |
| 2" x 1" CPVC 80 Reducing Coupling (SxS) | 9829249 | 1.562 | 0.355 | 1.133 | 3.05 | 1.52 | 3.04 | 0.875 | 1.75 | 0.565 | Socket 2" |
| 2" x 1-1/4" CPVC 80 Reducing Coupling (SxS) | 9829250 | 1.562 | 0.126 | 1.312 | 3 | 1.52 | 3.04 | 1.065 | 2.13 | 0.75 | Socket 2" |
| 2" x 1-1/2" CPVC 80 Reducing Coupling (SxS) | 9829251 | 1.562 | 0.107 | 1.381 | 3.05 | 1.52 | 3.04 | 1.252 | 2.504 | 0.76 | Socket 2" |
| 2-1/2" x 1/2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829287FB | 1.822 | 0.918 | 0.903 | 3.643 | 1.813 | 3.627 | 1.195 | 2.39 | 0.307 | Socket 2-1/2" |
| 2-1/2" x 3/4" CPVC 80 Reducing Coupling (SxS), Bushed | 9829288FB | 1.822 | 0.814 | 1.007 | 3.643 | 1.813 | 3.627 | 1.23 | 2.459 | 0.411 | Socket 2-1/2" |
| 2-1/2" x 1" CPVC 80 Reducing Coupling (SxS), Bushed | 9829289FB | 1.759 | 0.687 | 1.141 | 3.586 | 1.81 | 3.62 | 1.063 | 2.125 | 0.52 | Socket 2-1/2" |
| 2-1/2" x 1-1/4" CPVC 80 Reducing Coupling (SxS), Bushed | 9829290FB | 1.822 | 0.589 | 1.272 | 3.683 | 1.813 | 3.627 | 1.23 | 2.459 | 0.687 | Socket 2-1/2" |
| 2-1/2" x 1-1/2" CPVC 80 Reducing Coupling (SxS) | 9829291 | 1.759 | 0.14 | 1.381 | 3.28 | 1.75 | 3.5 | 1.19 | 2.38 | 0.875 | Socket 2-1/2" |
| 2-1/2" x 2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829292FB | 1.789 | 0.649 | 1.63 | 4.067 | 1.744 | 3.488 | 1.772 | 3.545 | 1.03 | Socket |

| | | | | | | | | | | | |
|---|-----------|-------|-------|-------|--------|-------|-------|-------|-------|-------|-----------|
| 3" x 1" CPVC 80 Reducing Coupling (SxS), Bushed | 9829335FB | 1.933 | 0.85 | 1.143 | 3.926 | 2.267 | 4.533 | 1.52 | 3.039 | 0.524 | Socket 3" |
| 3" x 1-1/2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829337FB | 1.893 | 1.173 | 1.501 | 4.567 | 2.096 | 4.192 | 1.981 | 3.963 | 0.815 | Socket 3" |
| 3" x 2" CPVC 80 Reducing Coupling (SxS) | 9829338 | 1.945 | 0.165 | 1.5 | 3.61 | 2.196 | 4.391 | 1.515 | 3.03 | 0.98 | Socket 3" |
| 3" x 2-1/2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829339FB | 1.893 | 0.678 | 1.843 | 4.413 | 2.096 | 4.192 | 1.981 | 3.963 | 1.2 | Socket 3" |
| 4" x 1" CPVC 80 Reducing Coupling (SxS), Bushed | 9829417FB | 2.304 | 1.487 | 1.141 | 4.932 | 2.828 | 5.655 | 2.208 | 4.416 | 0.52 | Socket 4" |
| 4" x 1-1/2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829419FB | 2.304 | 1.103 | 1.542 | 4.949 | 2.828 | 5.655 | 2.208 | 4.416 | 0.761 | Socket 4" |
| 4" x 2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829420FB | 2.304 | 0.217 | 1.861 | 4.382 | 2.828 | 5.655 | 2.208 | 4.416 | 1.454 | Socket 4" |
| 4" x 2-1/2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829421FB | 2.304 | 0.593 | 1.894 | 4.791 | 2.828 | 5.655 | 2.208 | 4.416 | 1.225 | Socket 4" |
| 4" x 3" CPVC 80 Reducing Coupling (SxS) | 9829422 | 2.253 | 0.254 | 1.883 | 4.39 | 2.763 | 5.527 | 2.204 | 4.407 | 1.46 | Socket 4" |
| 6" x 1-1/2" CPVC 80 Reducing Coupling (SxS), Bushed, 3 Step | 9829527FB | 3.04 | 2.937 | 1.486 | 7.463 | 3.78 | 7.56 | 1.981 | 3.963 | 0.815 | Socket 6" |
| 6" x 2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829528FB | 4.456 | 4.602 | 1.562 | 10.62 | 3.959 | 7.919 | 2.755 | 5.51 | 1 | Socket 6" |
| 6" x 2-1/2" CPVC 80 Reducing Coupling (SxS), Bushed, 2 Step | 9829529FB | 3.04 | 2.442 | 1.843 | 7.325 | 3.78 | 7.56 | 1.845 | 3.69 | 1.2 | Socket 6" |
| 6" x 3" CPVC 80 Reducing Coupling (SxS), Bushed | 9829530FB | 4.456 | 4.23 | 1.966 | 10.652 | 3.959 | 7.919 | 2.813 | 5.626 | 1.654 | Socket 6" |
| 6" x 4" CPVC 80 Reducing Coupling (SxS) | 9829532 | 4.456 | 3.456 | 2.26 | 10.172 | 3.959 | 7.919 | 2.755 | 5.51 | 1.943 | Socket 6" |
| 8" x 4" CPVC 80 Reducing Coupling (SxS), Bushed | 9829582FB | 4.033 | 2.107 | 3.037 | 9.176 | 4.9 | 9.8 | 3.903 | 7.806 | 3.074 | Socket 8" |
| 8" x 6" CPVC 80 Reducing Coupling (SxS) | 9829585 | 4.033 | 2.107 | 3.037 | 9.176 | 4.9 | 9.8 | 3.903 | 7.806 | 3.074 | Socket 8" |

| Part name | Part no. | End Type 2 | Operating Temperature 1 [°F] | Operating Temperature 2 [°F] | Weight per UOM [lbs/UOM] |
|---|-----------|---------------|----------------------------------|-----------------------------------|--------------------------|
| 3/4" x 1/2" CPVC 80 Reducing Coupling (SxS) | 9829101 | Socket 1/2" | 73 °F (23 °C) at 690 psi (23 °C) | 180 °F (82 °C) at 170 psi (82 °C) | 0.1 |
| 1" x 1/2" CPVC 80 Reducing Coupling (SxS) | 9829130 | Socket 1/2" | 73 °F (23 °C) at 630 psi (23 °C) | 180 °F (82 °C) at 155 psi (82 °C) | 0.14 |
| 1" x 3/4" CPVC 80 Reducing Coupling (SxS) | 9829131 | Socket 3/4" | 73 °F (23 °C) at 630 psi (23 °C) | 180 °F (82 °C) at 155 psi (82 °C) | 0.15 |
| 1-1/4" x 3/4" CPVC 80 Reducing Coupling (SxS), Bushed | 9829167FB | Socket 3/4" | 73 °F (23 °C) at 520 psi (23 °C) | 180 °F (82 °C) at 130 psi (82 °C) | 0.18 |
| 1-1/4" x 1" CPVC 80 Reducing Coupling (SxS), Bushed | 9829168FB | Socket 1" | 73 °F (23 °C) at 520 psi (23 °C) | 180 °F (82 °C) at 130 psi (82 °C) | 0.37 |
| 1-1/2" x 1/2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829209FB | Socket 1/2" | 73 °F (23 °C) at 470 psi (23 °C) | 180 °F (82 °C) at 115 psi (82 °C) | 0.23 |
| 1-1/2" x 3/4" CPVC 80 Reducing Coupling (SxS), Bushed | 9829210FB | Socket 3/4" | 73 °F (23 °C) at 470 psi (23 °C) | 180 °F (82 °C) at 115 psi (82 °C) | 0.94 |
| 1-1/2" x 1" CPVC 80 Reducing Coupling (SxS) | 9829211 | Socket 1" | 73 °F (23 °C) at 470 psi (23 °C) | 180 °F (82 °C) at 115 psi (82 °C) | 0.29 |
| 1-1/2" x 1-1/4" CPVC 80 Reducing Coupling (SxS) | 9829212 | Socket 1-1/4" | 73 °F (23 °C) at 470 psi (23 °C) | 180 °F (82 °C) at 115 psi (82 °C) | 0.29 |
| 2" x 1/2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829247FB | Socket 1/2" | 73 °F (23 °C) at 400 psi (23 °C) | 180 °F (82 °C) at 100 psi (82 °C) | 0.3 |
| 2" x 3/4" CPVC 80 Reducing Coupling (SxS), Bushed | 9829248FB | Socket 3/4" | 73 °F (23 °C) at 400 psi (23 °C) | 180 °F (82 °C) at 100 psi (82 °C) | 0.61 |
| 2" x 1" CPVC 80 Reducing Coupling (SxS) | 9829249 | Socket 1" | 73 °F (23 °C) at 400 psi (23 °C) | 180 °F (82 °C) at 100 psi (82 °C) | 0.62 |
| 2" x 1-1/4" CPVC 80 Reducing Coupling (SxS) | 9829250 | Socket 1-1/4" | 73 °F (23 °C) at 400 psi (23 °C) | 180 °F (82 °C) at 100 psi (82 °C) | 0.71 |
| 2" x 1-1/2" CPVC 80 Reducing Coupling (SxS) | 9829251 | Socket 1-1/2" | 73 °F (23 °C) at 400 psi (23 °C) | 180 °F (82 °C) at 100 psi (82 °C) | 0.71 |
| 2-1/2" x 1/2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829287FB | Socket 1/2" | 73 °F (23 °C) at 420 psi (23 °C) | 180 °F (82 °C) at 105 psi (82 °C) | 0.66 |
| 2-1/2" x 3/4" CPVC 80 Reducing Coupling (SxS), Bushed | 9829288FB | Socket 3/4" | 73 °F (23 °C) at 420 psi (23 °C) | 180 °F (82 °C) at 105 psi (82 °C) | 0.67 |

| | | | | | |
|---|-----------|---------------|----------------------------------|-----------------------------------|-------|
| 2-1/2" x 1" CPVC 80 Reducing Coupling (SxS), Bushed | 9829289FB | Socket 1" | 73 °F (23 °C) at 420 psi (23 °C) | 180 °F (82 °C) at 105 psi (82 °C) | 0.64 |
| 2-1/2" x 1-1/4" CPVC 80 Reducing Coupling (SxS), Bushed | 9829290FB | Socket 1-1/4" | 73 °F (23 °C) at 420 psi (23 °C) | 180 °F (82 °C) at 105 psi (82 °C) | 0.59 |
| 2-1/2" x 1-1/2" CPVC 80 Reducing Coupling (SxS) | 9829291 | Socket 1-1/2" | 73 °F (23 °C) at 420 psi (23 °C) | 180 °F (82 °C) at 105 psi (82 °C) | 0.8 |
| 2-1/2" x 2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829292FB | Socket 2" | 73 °F (23 °C) at 420 psi (23 °C) | 180 °F (82 °C) at 105 psi (82 °C) | 1.2 |
| 3" x 1" CPVC 80 Reducing Coupling (SxS), Bushed | 9829335FB | Socket 1" | 73 °F (23 °C) at 370 psi (23 °C) | 180 °F (82 °C) at 90 psi (82 °C) | 0.7 |
| 3" x 1-1/2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829337FB | Socket 1-1/2" | 73 °F (23 °C) at 370 psi (23 °C) | 180 °F (82 °C) at 90 psi (82 °C) | 0.93 |
| 3" x 2" CPVC 80 Reducing Coupling (SxS) | 9829338 | Socket 2" | 73 °F (23 °C) at 370 psi (23 °C) | 180 °F (82 °C) at 90 psi (82 °C) | 1 |
| 3" x 2-1/2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829339FB | Socket 2-1/2" | 73 °F (23 °C) at 370 psi (23 °C) | 180 °F (82 °C) at 90 psi (82 °C) | 1.56 |
| 4" x 1" CPVC 80 Reducing Coupling (SxS), Bushed | 9829417FB | Socket 1" | 73 °F (23 °C) at 320 psi (23 °C) | 180 °F (82 °C) at 80 psi (82 °C) | 2.43 |
| 4" x 1-1/2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829419FB | Socket 1-1/2" | 73 °F (23 °C) at 320 psi (23 °C) | 180 °F (82 °C) at 80 psi (82 °C) | 2.56 |
| 4" x 2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829420FB | Socket 2" | 73 °F (23 °C) at 320 psi (23 °C) | 180 °F (82 °C) at 80 psi (82 °C) | 2.61 |
| 4" x 2-1/2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829421FB | Socket 2-1/2" | 73 °F (23 °C) at 320 psi (23 °C) | 180 °F (82 °C) at 80 psi (82 °C) | 2.33 |
| 4" x 3" CPVC 80 Reducing Coupling (SxS) | 9829422 | Socket 3" | 73 °F (23 °C) at 320 psi (23 °C) | 180 °F (82 °C) at 80 psi (82 °C) | 1.82 |
| 6" x 1-1/2" CPVC 80 Reducing Coupling (SxS), Bushed, 3 Step | 9829527FB | Socket 1-1/2" | 73 °F (23 °C) at 280 psi (23 °C) | 180 °F (82 °C) at 70 psi (82 °C) | 8.23 |
| 6" x 2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829528FB | Socket 2" | 73 °F (23 °C) at 280 psi (23 °C) | 180 °F (82 °C) at 70 psi (82 °C) | 2.09 |
| 6" x 2-1/2" CPVC 80 Reducing Coupling (SxS), Bushed, 2 Step | 9829529FB | Socket 2-1/2" | 73 °F (23 °C) at 280 psi (23 °C) | 180 °F (82 °C) at 70 psi (82 °C) | 8.23 |
| 6" x 3" CPVC 80 Reducing Coupling (SxS), Bushed | 9829530FB | Socket 3" | 73 °F (23 °C) at 280 psi (23 °C) | 180 °F (82 °C) at 70 psi (82 °C) | 8.23 |
| 6" x 4" CPVC 80 Reducing Coupling (SxS) | 9829532 | Socket 4" | 73 °F (23 °C) at 280 psi (23 °C) | 180 °F (82 °C) at 70 psi (82 °C) | 7.3 |
| 8" x 4" CPVC 80 Reducing Coupling (SxS), Bushed | 9829582FB | Socket 4" | 73 °F (23 °C) at 250 psi (23 °C) | 180 °F (82 °C) at 60 psi (82 °C) | 13.44 |
| 8" x 6" CPVC 80 Reducing Coupling (SxS) | 9829585 | Socket 6" | 73 °F (23 °C) at 250 psi (23 °C) | 180 °F (82 °C) at 60 psi (82 °C) | 8.23 |

| Part name | Part no. | Codes | Standards | Listings |
|---|-----------|------------------------------|---------------------------------------|----------------------------|
| ChlorFIT Fitting Coupling Reducing | All | UPC IBC IRC IPC UMC NSPC IMC | ASTM F439 NSF/ANSI/CAN 61 NSF/ANSI 14 | ULC NSFpw-G IAPMO U.P.Code |
| In addition, the following parts have additional codes, standards, or listings: | | | | |
| 3/4" x 1/2" CPVC 80 Reducing Coupling (SxS) | 9829101 | | | ICC-ES-PMG |
| 1" x 1/2" CPVC 80 Reducing Coupling (SxS) | 9829130 | | | ICC-ES-PMG |
| 1" x 3/4" CPVC 80 Reducing Coupling (SxS) | 9829131 | | | ICC-ES-PMG |
| 1-1/4" x 3/4" CPVC 80 Reducing Coupling (SxS), Bushed | 9829167FB | | | ICC-ES-PMG |
| 1-1/4" x 1" CPVC 80 Reducing Coupling (SxS), Bushed | 9829168FB | | | ICC-ES-PMG |
| 1-1/2" x 1/2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829209FB | | | ICC-ES-PMG |
| 1-1/2" x 3/4" CPVC 80 Reducing Coupling (SxS), Bushed | 9829210FB | | | ICC-ES-PMG |
| 1-1/2" x 1" CPVC 80 Reducing Coupling (SxS) | 9829211 | | | ICC-ES-PMG |
| 1-1/2" x 1-1/4" CPVC 80 Reducing Coupling (SxS) | 9829212 | | | ICC-ES-PMG |
| 2" x 1/2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829247FB | | | ICC-ES-PMG |
| 2" x 3/4" CPVC 80 Reducing Coupling (SxS), Bushed | 9829248FB | | | ICC-ES-PMG |
| 2" x 1" CPVC 80 Reducing Coupling | 9829249 | | | ICC-ES-PMG |

| | | |
|---|-----------|------------|
| (SxS) | | |
| 2" x 1-1/4" CPVC 80 Reducing Coupling (SxS) | 9829250 | ICC-ES-PMG |
| 2" x 1-1/2" CPVC 80 Reducing Coupling (SxS) | 9829251 | ICC-ES-PMG |
| 2-1/2" x 1/2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829287FB | ICC-ES-PMG |
| 2-1/2" x 3/4" CPVC 80 Reducing Coupling (SxS), Bushed | 9829288FB | ICC-ES-PMG |
| 2-1/2" x 1" CPVC 80 Reducing Coupling (SxS), Bushed | 9829289FB | ICC-ES-PMG |
| 2-1/2" x 1-1/4" CPVC 80 Reducing Coupling (SxS), Bushed | 9829290FB | ICC-ES-PMG |
| 2-1/2" x 1-1/2" CPVC 80 Reducing Coupling (SxS) | 9829291 | ICC-ES-PMG |
| 2-1/2" x 2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829292FB | ICC-ES-PMG |
| 3" x 1" CPVC 80 Reducing Coupling (SxS), Bushed | 9829335FB | ICC-ES-PMG |
| 3" x 1-1/2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829337FB | ICC-ES-PMG |
| 3" x 2" CPVC 80 Reducing Coupling (SxS) | 9829338 | ICC-ES-PMG |
| 3" x 2-1/2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829339FB | ICC-ES-PMG |
| 4" x 1" CPVC 80 Reducing Coupling (SxS), Bushed | 9829417FB | ICC-ES-PMG |
| 4" x 1-1/2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829419FB | ICC-ES-PMG |
| 4" x 2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829420FB | ICC-ES-PMG |
| 4" x 2-1/2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829421FB | ICC-ES-PMG |
| 4" x 3" CPVC 80 Reducing Coupling (SxS) | 9829422 | ICC-ES-PMG |
| 6" x 1-1/2" CPVC 80 Reducing Coupling (SxS), Bushed, 3 Step | 9829527FB | ICC-ES-PMG |
| 6" x 2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829528FB | ICC-ES-PMG |
| 6" x 2-1/2" CPVC 80 Reducing Coupling (SxS), Bushed, 2 Step | 9829529FB | ICC-ES-PMG |
| 6" x 3" CPVC 80 Reducing Coupling (SxS), Bushed | 9829530FB | ICC-ES-PMG |
| 6" x 4" CPVC 80 Reducing Coupling (SxS) | 9829532 | ICC-ES-PMG |

| Installation | Related applications |
|---|-----------------------------------|
| Make connections via solvent welding using primer and solvent cement designed specifically for Schedule 80 CPVC pipe and fittings. Refer to the Uponor ChlorFIT Manual or Uponor ChlorFIT Solvent Welding Instruction Sheet for complete details. | Domestic water Hydronic piping |

| Footnotes | Contact information |
|-----------|---|
| - | <p style="text-align: center;">Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008</p> <p style="text-align: center;">Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517</p> |