

ChlorFIT Flanges Blind

Project Information

| | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Date submitted: |
| Contractor: | Submitted by: |
| Manufacturer's representative: | Approved by: |

Technical data

| | |
|-----------------------|-------------------------------------|
| Material | CPVC |
| Temp/pressure ratings | 73 °F (23 °C) at 150 psi (10.3 bar) |

Product information and application use

Use Uponor ChlorFIT® Schedule 80 Corzan® CPVC Blind Flanges in hot and cold potable-water systems as well as hydronic heating and cooling applications.



| Part name | Part no. | A [Inch] | B [Inch] | C [Inch] | D [Inch] | E [Inch] | F [Inch] | G [Inch] | H [Inch] | End Type 1 | Weight per UOM [lbs/UOM] |
|----------------------------|----------|----------|----------|----------|----------|----------|----------|----------|----------|---------------|--------------------------|
| 1/2" CPVC80 Blind Flange | 9853005 | 3.5 | 2.38 | 0.5 | 4 | 0.25 | 0.25 | 0.5 | 0.58 | Flange 1/2" | 0.28 |
| 3/4" CPVC80 Blind Flange | 9853007 | 3.88 | 2.75 | 0.5 | 4 | 0.25 | 0.25 | 0.5 | 0.695 | Flange 3/4" | 0.21 |
| 1" CPVC80 Blind Flange | 9853010 | 4.25 | 3.13 | 0.5 | 4 | 0.3 | 0.3 | 0.6 | 0.855 | Flange 1" | 0.3 |
| 1-1/4" CPVC80 Blind Flange | 9853012 | 4.63 | 3.5 | 0.5 | 4 | 0.315 | 0.315 | 0.63 | 1.04 | Flange 1-1/4" | 0.36 |
| 1-1/2" CPVC80 Blind Flange | 9853015 | 5 | 3.88 | 0.5 | 4 | 0.41 | 0.41 | 0.82 | 1.168 | Flange 1-1/2" | 0.47 |
| 2" CPVC80 Blind Flange | 9853020 | 6 | 4.75 | 0.625 | 4 | 0.46 | 0.46 | 0.92 | 1.438 | Flange 2" | 0.66 |
| 2-1/2" CPVC80 Blind Flange | 9853025 | 7 | 5.5 | 0.625 | 4 | 0.48 | 0.48 | 0.96 | 1.75 | Flange 2-1/2" | 1.02 |
| 3" CPVC80 Blind Flange | 9853030 | 7.5 | 6 | 0.625 | 4 | 0.515 | 0.515 | 1.03 | 2.075 | Flange 3" | 1.6 |
| 4" CPVC80 Blind Flange | 9853040 | 9 | 7.5 | 0.625 | 8 | 0.675 | 0.675 | 1.35 | 2.615 | Flange 4" | 2.34 |
| 6" CPVC80 Blind Flange | 9853060 | 11 | 9.5 | 0.75 | 8 | 0.745 | 0.745 | 1.49 | 3.78 | Flange 6" | 3.79 |
| 8" CPVC80 Blind Flange | 9853080 | 13.5 | 11.75 | 0.75 | 8 | 0.815 | 0.815 | 1.63 | 4.87 | Flange 8" | 6.09 |

| Part name | Part no. | Codes | Standards | Listings |
|------------------------|----------|------------------------------|-----------------------------|----------------------------|
| ChlorFIT Flanges Blind | All | UPC IBC IRC IPC UMC NSPC IMC | NSF/ANSI/CAN 61 NSF/ANSI 14 | ULC NSFpw-G IAPMO U.P.Code |

In addition, the following parts have additional codes, standards, or listings:

| | | | | |
|----------------------------|---------|--|--|------------|
| 1/2" CPVC80 Blind Flange | 9853005 | | | ICC-ES-PMG |
| 3/4" CPVC80 Blind Flange | 9853007 | | | ICC-ES-PMG |
| 1" CPVC80 Blind Flange | 9853010 | | | ICC-ES-PMG |
| 1-1/4" CPVC80 Blind Flange | 9853012 | | | ICC-ES-PMG |
| 1-1/2" CPVC80 Blind Flange | 9853015 | | | ICC-ES-PMG |
| 2" CPVC80 Blind Flange | 9853020 | | | ICC-ES-PMG |
| 2-1/2" CPVC80 Blind Flange | 9853025 | | | ICC-ES-PMG |
| 3" CPVC80 Blind Flange | 9853030 | | | ICC-ES-PMG |
| 4" CPVC80 Blind Flange | 9853040 | | | ICC-ES-PMG |
| 6" CPVC80 Blind Flange | 9853060 | | | ICC-ES-PMG |

Installation

Make connections via solvent welding using primer and solvent cement designed specifically for Schedule 80 CPVC pipe and fittings. Refer to the Uponor ChlorFIT Manual or Uponor ChlorFIT Solvent Welding Instruction Sheet for complete details.

Related applications

Domestic water
Hydronic piping

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517