

Actuadores térmicos de dos cables para colectores con válvulas TruFLOW Classic y TruFLOW Jr.



Project information


| | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Fecha de envío: |
| Contractor: | Presentada por: |
| Manufacturer's representative: | Approved by: |

Technical data

Prop 65 label required? Yes

Product information and application use

The Uponor Two-wire Thermal Actuators are slow-opening thermal actuators that mount directly onto Uponor manifolds. They provide individual-loop flow control on multi-zoned manifolds.



| Part name | Part no. | A [inch] | B [inch] | C [inch] | Current draw max. [A] | Operating voltage AC [VAC] | Weight per UOM [lbs/UOM] |
|--|----------|----------|----------|----------|-----------------------|----------------------------|--------------------------|
| Two-wire Thermal Actuator for TruFLOW Classic and Jr. Valved Manifolds | A3030523 | 2.86 | 1.56 | 1.56 | 0.083 | 24 | 0.25 |

| Part name | Part no. | Codes | Standards | Listings |
|--|----------|-------|-----------------|----------|
| Actuadores térmicos de dos cables para colectores con válvulas TruFLOW Classic y TruFLOW Jr. | A3030523 | - | Class II wiring | - |

Installation

Mount directly onto the manifold. Refer to the manifold installation guide for detailed instructions.

Related applications

- Radiant Heating and Cooling Systems
- Permafrost Protection Systems
- Turf Conditioning Systems

Notes

Time to Open/Close:
3 to 5 minutes

Footnotes

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517