

Colectores sin válvula de cobre (tipo L)

Project information

Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

Technical data

Material	Copper
End type 1	Sweat 3/4"
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar)
	180 °F (82 °C) at 100 psi (6.9 bar)
	200 °F (93 °C) at 80 psi (5.5 bar)
	210 °F (99 °C) at 149 psi (10.3 bar)
Prop 65 label required?	Yes

Product information and application use



Use the Uponor 2" Copper Valveless Manifold in hot and cold domestic potable water distribution systems or balanced radiant heating and/or cooling systems that do not require individual loop control. The manifold features 3/4" sweat connections

This product is made to order, please contact [customer service](#) for lead time.

Part name	Part no.	A [inch]	B [inch]	C [inch]	Manifold Body Size (I.D.) [inch]	Flow Rate Max. [gpm]	Weight per UOM [lbs/UOM]
2" x 6' Copper Valveless Manifold with 24 outlets, 3/4" sweat	F2802075	72	4.125	2.125	2	45	12.35
1 1/2" x 6' Copper Valveless Manifold with 24 outlets, 3/4" sweat	F2801575	72	3.625	1.625	1.5	21	8.7

Part name	Part no.	Codes	Standards	Listings
Colectores sin válvula de cobre (tipo L)	All	UPC IPC NPC of Canada NSPC	CSA B137.5 ASTM F877	NSF 14- and 61-certified

Installation

Use any product designed to mount 2" copper pipe as a mounting bracket. Any bend within 6 inches of the connection to the manifold requires the use of a tube talon (F7050750) or bend supports (A5110750 or A5150750)

Related applications

PEX-a Plumbing Systems
Radiant Heating and Cooling Systems

Footnotes

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517