

Cajas para equipos para fabricar hielo de bronce sin plomo (LF) ProPEX



Project Information

| | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Fecha de envío: |
| Contractor: | Presentada por: |
| Manufacturer's representative: | Approved by: |

Technical data

| | |
|-----------------------|-------------------------------------|
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar) |
| | 180 °F (82 °C) at 100 psi (6.9 bar) |
| | 200 °F (93 °C) at 80 psi (5.5 bar) |

Product information and application use

The ProPEX® Ice Maker Box with Support Brackets, 1/2" (LF Brass) Valve with snap-in frame includes a 1/2" lead-free brass valve with 1/4" O.D. compression connection. This high-impact box is an aesthetic, convenient option for connecting to standard ice maker tubing. Two support brackets are provided for easy mounting.



Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.

| Part name | Part no. | A [inch] | B [inch] | C [inch] | Material group | End Type 1 | End Type 2 | Prop 65 label required? | Weight per UOM [lbs/UOM] |
|---|-----------|----------|----------|----------|-----------------|------------|-------------|-------------------------|--------------------------|
| ProPEX Ice Maker Box with Support Brackets, 1/2" LF Brass Valve | LF5955025 | 20.29 | 6 | 3.55 | - | ProPEX | Compression | Yes | 0.87 |
| 1/4" Insert (stainless steel) | F5400250 | 0.719 | 0.323 | 0.323 | Stainless Steel | - | - | - | 0 |

| Part name | Part no. | Codes | Standards | Listings |
|--|----------|-----------------------|--|----------------------|
| Cajas para equipos para fabricar hielo de bronce sin plomo (LF) ProPEX | All | UPC IPC NPC of Canada | ASME A112.18.1 NSF/ANSI/CAN 372 ASTM F877 ASTM F1960 CSA B125 CSA B137.5 NSF/ANSI/CAN 61 NSF/ANSI 14 | cNSFus-pw-G U.P.Code |

Installation

Mount in wall cavity at the desired location (e.g., behind refrigerator) using the supplied mounting brackets or directly to studs. For more information, refer to the AquaPEX® Professional Plumbing Installation Guide.

Related applications

PEX-a Plumbing Systems

Footnotes

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517