

Cajas de salida para lavadoras de bronce sin plomo (LF) ProPEX



Project Information

Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

Technical data

Material	LF Brass
Subcomponent Material	Box: High-impact polystyrene Frame: High-impact polystyrene Support Brackets: High-impact polystyrene Valve: LF Brass
Prop 65 label required?	Yes



Product Information and application use

Uponor's ProPEX® Washing Machine Outlet Box comes with two 1/2" ProPEX hot and cold, color-coded, lead-free brass valves. The valves may be mounted from the top or bottom. The four support brackets provide easy mounting between studs. The snap-on frame (included) accommodates up to 1" drywall.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.

Part name	Part no.	A [inch]	B [inch]	C [inch]	Weight per UOM [lbs/UOM]
ProPEX Washing Machine Outlet Box, 1/2" LF Brass Valves	LF5930500	25.03	8.786	3.731	1.95

Part name	Part no.	Codes	Standards	Listings
Cajas de salida para lavadoras de bronce sin plomo (LF) ProPEX	LF5930500	UPC IPC NPC of Canada	NSF-372 ASME A112.18.1 ASTM F877 ASTM F1960 CSA B125 CSA B137.5 NSF-61 NSF-14	cNSFus-pw-G U.P.Code

Installation

Mount in wall cavity at the desired location (e.g., behind washing machine) using the supplied mounting brackets or directly to studs. For more information, refer to the AquaPEX® Professional Plumbing Installation Guide.

Related applications

PEX-a Plumbing Systems

Footnotes

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517