

Colectores sin válvula de cobre y con conexiones ProPEX

Project Information

Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

Technical data

Material	Copper
Manifold size	2 inch
End type 1	ProPEX 3/4"
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar) 210 °F (99 °C) at 149 psi (10.3 bar)
Max. fluid flow rate	45 gpm
Prop 65 label required?	Yes



Product Information and application use

The 2" Copper Valveless Manifold with ProPEX® Connection is used for radiant heating projects. The manifold has a 2" copper sweat fitting adapter supply connection and 3/4" nominal branches. This 12-outlet manifold is preassembled with 5/8" or 3/4" ProPEX connections.

This product is made to order, please contact customer service for lead time.

Part name	Part no.	A [inch]	B [inch]	C [inch]	Weight per UOM [lbs/UOM]
2" x 4' Copper Valveless Manifold with 3/4" ProPEX, 12 outlets	Q2831275	48	5.238	2.125	10.5

Part name	Part no.	Codes	Standards	Listings
Colectores sin válvula de cobre y con conexiones ProPEX	Q2831275	-	CSA B137.5 ASTM F877	cNSFus-rfh

Installation

Any product designed to mount 2" copper pipe may be used as a mounting bracket. Refer to the Uponor Radiant Installation Handbook for additional information. Accessories: 2" Copper Manifold End Cap (A2402000).

Related applications

Radiant Heating and Cooling Systems

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517