

Tapones de bronce ProPEX

Project Information

Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

Technical data

Material	Brass
End type 1	ProPEX 5/8"
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)
Prop 65 label required?	Yes

Product Information and application use

Uponor 5/8" ProPEX® Brass Plug is available for use in any hydronic heating and/or cooling system. The end of the plug is manufactured with the Uponor ProPEX Fitting for connections to Uponor crosslinked polyethylene (PEX) tubing.



Part name	Part no.	A [inch]	B [inch]	C [inch]	D [inch]	Weight per UOM [lbs/UOM]
ProPEX Brass Plug for 5/8" PEX	Q4536363	0.991	1.04	1.04	0.866	0.06

Part name	Part no.	Codes	Standards	Listings
Tapones de bronce ProPEX	Q4536363	IMC IBC IRC NPC of Canada UMC	ASTM F1960 CSA B137.5 NSF/ANSI 14 ASTM F877	IAPMO-ES ICC-ES-PMG cNSFus-rfh

Installation

Use a 5/8" ProPEX Ring with Stop (Q4690625) for the tubing. For more information, refer to the Uponor ProPEX Connections Instructional Guide.

Related applications

- Radiant Heating and Cooling Systems
- Permafrost Prevention Systems
- Turf Conditioning Systems

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517