

# Soportes de tuberías PEX-a

## Project Information

|                                |                 |
|--------------------------------|-----------------|
| Job name:                      | Location:       |
| Engineer:                      | Fecha de envío: |
| Contractor:                    | Presentada por: |
| Manufacturer's representative: | Approved by:    |

## Product information and application use

PEX-a Pipe Support is a non-combustible, self-gripping, galvanized-steel channel for crosslinked polyethylene (PEX-a) pipe. It provides continuous, uninterrupted support of PEX-a pipe, allowing hanger placement similar to that of metallic pipe. Use PEX-a Pipe Support in conjunction with un-insulated Uponor AquaPEX® or Wirsbo hePEX™ PEX-a pipe in ASTM E84 plenum applications. The PEX-a pipe with pipe support can be insulated with typical CTS (copper tube size) pipe insulation. PEX-a Pipe Support is offered in 9-foot lengths and comes with nylon-coated, stainless-steel strapping.



| Part name  | Part no. | A [inch] | B [inch] | C [inch] | Material group | Subcomponent Material                      | Prop 65 label required? | Weight per UOM [lbs/UOM] |
|--|----------|----------|----------|----------|----------------|--|-------------------------|--------------------------|
| 1/2" PEX-a Pipe Support, 9-ft. length                      | F7040500 | 108      | 0.677    | 0.406    | Metal          | Commercial-grade (Type B) galvanized steel | -                       | 1.1                      |
| 3/4" PEX-a Pipe Support, 9-ft. length                      | F7040750 | 108      | 0.921    | 0.552    | Metal          | Commercial-grade (Type B) galvanized steel | No                      | 1.5                      |
| 1" PEX-a Pipe Support, 9-ft. length                        | F7041000 | 108      | 1.163    | 0.698    | Metal          | Commercial-grade (Type B) galvanized steel | -                       | 1.91                     |
| 1 1/4" PEX-a Pipe Support, 9-ft. length                    | F7041250 | 108      | 1.396    | 0.837    | Metal          | Commercial-grade (Type B) galvanized steel | -                       | 2.1                      |
| 1 1/2" PEX-a Pipe Support, 9-ft. length                    | F7041500 | 108      | 1.623    | 0.973    | Metal          | Commercial-grade (Type B) galvanized steel | -                       | 2.5                      |
| 2" PEX-a Pipe Support, 9-ft. length                        | F7042000 | 108      | 2.095    | 1.256    | Metal          | Commercial-grade (Type B) galvanized steel | -                       | 3.6                      |
| 2 1/2" PEX-a Pipe Support, 9-ft. length                    | F7042500 | 108      | 2.562    | 1.537    | Metal          | Commercial-grade (Type B) galvanized steel | -                       | 4.6                      |
| PEX-a Pipe Support Strapping for 1/2", 3/4" and 1" PEX     | Q7410510 | -        | -        | -        | Plastic        | -  | -                       | 0                        |
| 3" PEX-a Pipe Support, 9-ft. length                        | F7043000 | 108      | 3.024    | 1.81     | Metal          | Commercial-grade (Type B) galvanized steel | -                       | 6.2                      |
| PEX-a Pipe Support Strapping for 1 1/4", 1 1/2" and 2" PEX | Q7411220 | -        | -        | -        | Plastic        | -  | -                       | 0.01                     |
| PEX-a Pipe Support Strapping for 2 1/2", 3", 3 1/2" PEX    | Q7412540 | -        | -        | -        | Plastic        | -  | -                       | 0.01                     |

| Part name                  | Part no. | Codes   | Standards | Listings            |
|----------------------------|----------|---------|-----------|---------------------|
| Soportes de tuberías PEX-a | All      | IMC UMC | ASTM E84  | QAI P321 (up to 3") |

## Installation

Install PEX-a Pipe Support vertically or horizontally for plenum and non-plenum applications. Refer to the Uponor PEX-a Pipe Support Instruction Sheet for installation guidelines.

## Related applications

- PEX-a Plumbing Systems
- Radiant Heating and Cooling Systems
- AquaSAFE™ Fire Safety Systems

Uponor Inc.  
5925 148th Street West  
Apple Valley, MN 55124  
T 800.321.4739  
F 952.891.2008

Uponor Ltd.  
6510 Kennedy Road  
Mississauga, ON L5T 2X4  
T 888.594.7726  
F 800.638.9517

---