

Colectores con válvula de cobre y válvulas de bola y compensación ProPEX



Project Information

| | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Fecha de envío: |
| Contractor: | Presentada por: |
| Manufacturer's representative: | Approved by: |

Technical data

| | |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Material | Copper |
| Manifold size | 2 inch |
| Loop Cv | 6.7 Cv |
| End type 1 | ProPEX 3/4" |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar) 210 °F (99 °C) at 149 psi (10.3 bar) |
| Max. fluid flow rate | 45 gpm |
| Prop 65 label required? | Yes |



Product information and application use

Uponor offers 2" Copper Valved Manifold with ProPEX® Ball and Balancing Valves for radiant heating projects. The manifold has a 2" Copper Sweat Fitting Adapter supply connection and 3/4" nominal branches. This 12-outlet manifold is preassembled with 5/8" or 3/4" ProPEX balancing valve connections.

This product is made to order, please contact customer service for lead time.

| Part name | Part no. | A [inch] | B [inch] | C [inch] | Weight per UOM [lbs/UOM] |
|---------------------------------------------------------------------------------------|----------|----------|----------|----------|--------------------------|
| 2" x 4' Copper Valved Manifold with 3/4" ProPEX Ball and Balancing Valves, 12 outlets | Q2821275 | 48 | 7.871 | 2.633 | 15.25 |

| Part name | Part no. | Codes | Standards | Listings |
|--------------------------------------------------------------------------|----------|-------|----------------------|------------|
| Colectores con válvula de cobre y válvulas de bola y compensación ProPEX | Q2821275 | - | CSA B137.5 ASTM F877 | cNSFus-rfh |

Installation

Install using any product designed to mount 2" copper pipe as a mounting bracket. Refer to the Uponor Radiant Floor Heating Installation Handbook for additional information.

Related applications

- Radiant Heating and Cooling Systems
- Permafrost Protection Systems
- Turf Conditioning Systems

Notes

- Ball Valve Cv " outlet: 6.60
- Ball Valve Cv 3/4" outlet: 6.70

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517