

Colectores con válvula de cobre y válvulas de bola con rosca R20/R25



Project Information

| | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Fecha de envío: |
| Contractor: | Presentada por: |
| Manufacturer's representative: | Approved by: |

Technical data

| | |
|-------------------------|--------------------------------------|
| Cv | 7 |
| Material | Copper |
| Manifold size | 2 inch |
| End type 1 | ISO 228-G 3/4" |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar) |
| | 180 °F (82 °C) at 100 psi (6.9 bar) |
| | 200 °F (93 °C) at 80 psi (5.5 bar) |
| | 210 °F (99 °C) at 149 psi (10.3 bar) |
| Max. fluid flow rate | 45 gpm |
| Prop 65 label required? | Yes |



Product information and application use

The 2" x 4' Copper Valved Manifold with R20/R25 Threaded Ball Valves is designed for radiant heating applications. The manifold has a 2" copper sweat fitting adapter supply connection and 3/4" nominal branches that are 4 inches on center. This 12-outlet manifold comes preassembled with R20 and R25 threaded ball valve connections.

This product is made to order, please contact [customer service](#) for lead time.

| Part name | Part no. | A [Inch] | B [Inch] | C [Inch] | Weight per UOM [lbs/UOM] |
|--|----------|----------|----------|----------|--------------------------|
| 2" x 4' Copper Valved Manifold with R20 Threaded Ball Valves, 12 outlets | F2811220 | 48 | 5.728 | 2.319 | 14.75 |

| Part name | Part no. | Codes | Standards | Listings |
|--|----------|-------|-------------------------------|------------|
| Colectores con válvula de cobre y válvulas de bola con rosca R20/R25 | F2811220 | - | CSA B125 CSA B137.5 ASTM F877 | cNSFus-rfh |

Installation

Install using any product designed to mount 2" copper pipe as a mounting bracket. Refer to the Uponor Radiant Floor Heating Installation Handbook for additional information.

Related applications

- Radiant Heating and Cooling Systems
- Permafrost Protection Systems
- Turf Conditioning Systems

Notes

Ball Cv for the R20 outlet:
7.00
Ball Cv for the R25 outlet: 7.30

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517