

# Colectores sin válvula de HDPE

## Project information

Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

## Product information and application use

Uponor offers the multiple-outlet HDPE Valveless Manifolds for applications with greater flow requirements (larger than 5,000 square feet). Manufactured with grade 303 stainless steel ProPEX® fittings (3/4" or 1") hydraulically pressed onto the outlet nipples, these manifolds are maintenance-free and suitable for direct burial. The HDPE Valveless Manifolds come with standard 12" on-center (o.c.) outlet spacing.

*This product is made to order, please contact [customer service](#) for lead time.*



## Installation

Connect HDPE tubing through fusion welding. Connect PEX tubing to outlets via ProPEX connection method. For additional information, refer to the Radiant Floor Heating Installation Handbook.

## Related applications

- Radiant Heating and Cooling Systems
- Permafrost Protection Systems
- Turf Conditioning Systems

## Footnotes

-

## Contact information

Uponor Inc.  
5925 148th Street West  
Apple Valley, MN 55124  
T 800.321.4739  
F 952.891.2008

Uponor Ltd.  
6510 Kennedy Road  
Mississauga, ON L5T 2X4  
T 888.594.7726  
F 800.638.9517