

Colectores sin válvula de HDPE

Project information

Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

Product information and application use

Uponor offers the multiple-outlet HDPE Valveless Manifolds for applications with greater flow requirements (larger than 5,000 square feet). Manufactured with grade 303 stainless steel ProPEX® fittings (3/4" or 1") hydraulically pressed onto the outlet nipples, these manifolds are maintenance-free and suitable for direct burial. The HDPE Valveless Manifolds come with standard 12" on-center (o.c.) outlet spacing.

This product is made to order, please contact [customer service](#) for lead time.



Installation

Connect HDPE tubing through fusion welding. Connect PEX tubing to outlets via ProPEX connection method. For additional information, refer to the Radiant Floor Heating Installation Handbook.

Related applications

- Radiant Heating and Cooling Systems
- Permafrost Protection Systems
- Turf Conditioning Systems

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517