

# ChlorFIT Acoplamiento de Accesorios Reductores

## Project Information

|                                |                 |
|--------------------------------|-----------------|
| Job name:                      | Location:       |
| Engineer:                      | Fecha de envío: |
| Contractor:                    | Presentada por: |
| Manufacturer's representative: | Approved by:    |

## Technical data

Material CPVC

## Product information and application use

Utilice los acoplamientos de CPVC Corzan® ChlorFIT® Schedule 80 de Uponor en sistemas de agua potable fría y caliente, así como en aplicaciones hidráulicas de calefacción y refrigeración.



| Part name                                               | Part no.  | A [Inch] | B [Inch] | C [Inch] | D [Inch] | E [Inch] | F [Inch] | G [Inch] | H [Inch] | I [Inch] | End Type 1    |
|---------------------------------------------------------|-----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|---------------|
| 3/4" x 1/2" CPVC 80 Reducing Coupling (SxS)             | 9829101   | 1.047    | 0.11     | 0.922    | 2.079    | 0.755    | 1.51     | 0.64     | 1.28     | 0.28     | Socket 3/4"   |
| 1" x 1/2" CPVC 80 Reducing Coupling (SxS)               | 9829130   | 1.188    | 0.1      | 0.922    | 2.21     | 0.925    | 1.85     | 0.64     | 1.28     | 0.28     | Socket 1"     |
| 1" x 3/4" CPVC 80 Reducing Coupling (SxS)               | 9829131   | 1.134    | 0.117    | 1.009    | 2.26     | 0.928    | 1.857    | 0.763    | 1.526    | 0.41     | Socket 1"     |
| 1-1/4" x 3/4" CPVC 80 Reducing Coupling (SxS), Bushed   | 9829167FB | 1.272    | 0.686    | 1.012    | 2.97     | 1.044    | 2.088    | 1.09     | 2.18     | 0.82     | Socket 1-1/4" |
| 1-1/4" x 1" CPVC 80 Reducing Coupling (SxS), Bushed     | 9829168FB | 1.272    | 0.567    | 1.148    | 2.987    | 1.044    | 2.088    | 1.089    | 2.178    | 0.525    | Socket 1-1/4" |
| 1-1/2" x 1/2" CPVC 80 Reducing Coupling (SxS), Bushed   | 9829209FB | 1.394    | 0.108    | 1.151    | 2.654    | 1.302    | 2.603    | 0.928    | 1.855    | 0.526    | Socket 1-1/2" |
| 1-1/2" x 3/4" CPVC 80 Reducing Coupling (SxS), Bushed   | 9829210FB | 1.394    | 0.52     | 1.022    | 2.937    | 1.302    | 2.603    | 0.928    | 1.855    | 0.411    | Socket 1-1/2" |
| 1-1/2" x 1" CPVC 80 Reducing Coupling (SxS)             | 9829211   | 1.438    | 0.124    | 1.188    | 2.75     | 1.25     | 2.5      | 0.925    | 1.85     | 0.525    | Socket 1-1/2" |
| 1-1/2" x 1-1/4" CPVC 80 Reducing Coupling (SxS)         | 9829212   | 1.438    | 0.1      | 1.312    | 2.85     | 1.25     | 2.5      | 1.065    | 2.13     | 0.645    | Socket 1-1/2" |
| 2" x 1/2" CPVC 80 Reducing Coupling (SxS), Bushed       | 9829247FB | 1.69     | 0.316    | 1.147    | 3.153    | 1.587    | 3.174    | 0.881    | 1.762    | 0.554    | Socket 2"     |
| 2" x 3/4" CPVC 80 Reducing Coupling (SxS), Bushed       | 9829248FB | 1.69     | 0.316    | 1.147    | 3.153    | 1.587    | 3.174    | 0.881    | 1.762    | 0.554    | Socket 2"     |
| 2" x 1" CPVC 80 Reducing Coupling (SxS)                 | 9829249   | 1.562    | 0.355    | 1.133    | 3.05     | 1.52     | 3.04     | 0.875    | 1.75     | 0.565    | Socket 2"     |
| 2" x 1-1/4" CPVC 80 Reducing Coupling (SxS)             | 9829250   | 1.562    | 0.126    | 1.312    | 3        | 1.52     | 3.04     | 1.065    | 2.13     | 0.75     | Socket 2"     |
| 2" x 1-1/2" CPVC 80 Reducing Coupling (SxS)             | 9829251   | 1.562    | 0.107    | 1.381    | 3.05     | 1.52     | 3.04     | 1.252    | 2.504    | 0.76     | Socket 2"     |
| 2-1/2" x 1/2" CPVC 80 Reducing Coupling (SxS), Bushed   | 9829287FB | 1.822    | 0.918    | 0.903    | 3.643    | 1.813    | 3.627    | 1.195    | 2.39     | 0.307    | Socket 2-1/2" |
| 2-1/2" x 3/4" CPVC 80 Reducing Coupling (SxS), Bushed   | 9829288FB | 1.822    | 0.814    | 1.007    | 3.643    | 1.813    | 3.627    | 1.23     | 2.459    | 0.411    | Socket 2-1/2" |
| 2-1/2" x 1" CPVC 80 Reducing Coupling (SxS), Bushed     | 9829289FB | 1.759    | 0.687    | 1.141    | 3.586    | 1.81     | 3.62     | 1.063    | 2.125    | 0.52     | Socket 2-1/2" |
| 2-1/2" x 1-1/4" CPVC 80 Reducing Coupling (SxS), Bushed | 9829290FB | 1.822    | 0.589    | 1.272    | 3.683    | 1.813    | 3.627    | 1.23     | 2.459    | 0.687    | Socket 2-1/2" |
| 2-1/2" x 1-1/2" CPVC 80 Reducing Coupling (SxS)         | 9829291   | 1.759    | 0.14     | 1.381    | 3.28     | 1.75     | 3.5      | 1.19     | 2.38     | 0.875    | Socket 2-1/2" |
| 2-1/2" x 2" CPVC 80 Reducing Coupling (SxS), Bushed     | 9829292FB | 1.789    | 0.649    | 1.63     | 4.067    | 1.744    | 3.488    | 1.772    | 3.545    | 1.03     | Socket        |

|                                                             |           |       |       |       |        |       |       |       |       |       |           |
|-------------------------------------------------------------|-----------|-------|-------|-------|--------|-------|-------|-------|-------|-------|-----------|
| 3" x 1" CPVC 80 Reducing Coupling (SxS), Bushed             | 9829335FB | 1.933 | 0.85  | 1.143 | 3.926  | 2.267 | 4.533 | 1.52  | 3.039 | 0.524 | Socket 3" |
| 3" x 1-1/2" CPVC 80 Reducing Coupling (SxS), Bushed         | 9829337FB | 1.893 | 1.173 | 1.501 | 4.567  | 2.096 | 4.192 | 1.981 | 3.963 | 0.815 | Socket 3" |
| 3" x 2" CPVC 80 Reducing Coupling (SxS)                     | 9829338   | 1.945 | 0.165 | 1.5   | 3.61   | 2.196 | 4.391 | 1.515 | 3.03  | 0.98  | Socket 3" |
| 3" x 2-1/2" CPVC 80 Reducing Coupling (SxS), Bushed         | 9829339FB | 1.893 | 0.678 | 1.843 | 4.413  | 2.096 | 4.192 | 1.981 | 3.963 | 1.2   | Socket 3" |
| 4" x 1" CPVC 80 Reducing Coupling (SxS), Bushed             | 9829417FB | 2.304 | 1.487 | 1.141 | 4.932  | 2.828 | 5.655 | 2.208 | 4.416 | 0.52  | Socket 4" |
| 4" x 1-1/2" CPVC 80 Reducing Coupling (SxS), Bushed         | 9829419FB | 2.304 | 1.103 | 1.542 | 4.949  | 2.828 | 5.655 | 2.208 | 4.416 | 0.761 | Socket 4" |
| 4" x 2" CPVC 80 Reducing Coupling (SxS), Bushed             | 9829420FB | 2.304 | 0.217 | 1.861 | 4.382  | 2.828 | 5.655 | 2.208 | 4.416 | 1.454 | Socket 4" |
| 4" x 2-1/2" CPVC 80 Reducing Coupling (SxS), Bushed         | 9829421FB | 2.304 | 0.593 | 1.894 | 4.791  | 2.828 | 5.655 | 2.208 | 4.416 | 1.225 | Socket 4" |
| 4" x 3" CPVC 80 Reducing Coupling (SxS)                     | 9829422   | 2.253 | 0.254 | 1.883 | 4.39   | 2.763 | 5.527 | 2.204 | 4.407 | 1.46  | Socket 4" |
| 6" x 1-1/2" CPVC 80 Reducing Coupling (SxS), Bushed, 3 Step | 9829527FB | 3.04  | 2.937 | 1.486 | 7.463  | 3.78  | 7.56  | 1.981 | 3.963 | 0.815 | Socket 6" |
| 6" x 2" CPVC 80 Reducing Coupling (SxS), Bushed             | 9829528FB | 4.456 | 4.602 | 1.562 | 10.62  | 3.959 | 7.919 | 2.755 | 5.51  | 1     | Socket 6" |
| 6" x 2-1/2" CPVC 80 Reducing Coupling (SxS), Bushed, 2 Step | 9829529FB | 3.04  | 2.442 | 1.843 | 7.325  | 3.78  | 7.56  | 1.845 | 3.69  | 1.2   | Socket 6" |
| 6" x 3" CPVC 80 Reducing Coupling (SxS), Bushed             | 9829530FB | 4.456 | 4.23  | 1.966 | 10.652 | 3.959 | 7.919 | 2.813 | 5.626 | 1.654 | Socket 6" |
| 6" x 4" CPVC 80 Reducing Coupling (SxS)                     | 9829532   | 4.456 | 3.456 | 2.26  | 10.172 | 3.959 | 7.919 | 2.755 | 5.51  | 1.943 | Socket 6" |
| 8" x 4" CPVC 80 Reducing Coupling (SxS), Bushed             | 9829582FB | 4.033 | 2.107 | 3.037 | 9.176  | 4.9   | 9.8   | 3.903 | 7.806 | 3.074 | Socket 8" |
| 8" x 6" CPVC 80 Reducing Coupling (SxS)                     | 9829585   | 4.033 | 2.107 | 3.037 | 9.176  | 4.9   | 9.8   | 3.903 | 7.806 | 3.074 | Socket 8" |

| Part name                                             | Part no.  | End Type 2    | Operating Temperature 1 [°F]     | Operating Temperature 2 [°F]      | Weight per UOM [lbs/UOM] |
|-------------------------------------------------------|-----------|---------------|----------------------------------|-----------------------------------|--------------------------|
| 3/4" x 1/2" CPVC 80 Reducing Coupling (SxS)           | 9829101   | Socket 1/2"   | 73 °F (23 °C) at 690 psi (23 °C) | 180 °F (82 °C) at 170 psi (82 °C) | 0.1                      |
| 1" x 1/2" CPVC 80 Reducing Coupling (SxS)             | 9829130   | Socket 1/2"   | 73 °F (23 °C) at 630 psi (23 °C) | 180 °F (82 °C) at 155 psi (82 °C) | 0.14                     |
| 1" x 3/4" CPVC 80 Reducing Coupling (SxS)             | 9829131   | Socket 3/4"   | 73 °F (23 °C) at 630 psi (23 °C) | 180 °F (82 °C) at 155 psi (82 °C) | 0.15                     |
| 1-1/4" x 3/4" CPVC 80 Reducing Coupling (SxS), Bushed | 9829167FB | Socket 3/4"   | 73 °F (23 °C) at 520 psi (23 °C) | 180 °F (82 °C) at 130 psi (82 °C) | 0.18                     |
| 1-1/4" x 1" CPVC 80 Reducing Coupling (SxS), Bushed   | 9829168FB | Socket 1"     | 73 °F (23 °C) at 520 psi (23 °C) | 180 °F (82 °C) at 130 psi (82 °C) | 0.37                     |
| 1-1/2" x 1/2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829209FB | Socket 1/2"   | 73 °F (23 °C) at 470 psi (23 °C) | 180 °F (82 °C) at 115 psi (82 °C) | 0.23                     |
| 1-1/2" x 3/4" CPVC 80 Reducing Coupling (SxS), Bushed | 9829210FB | Socket 3/4"   | 73 °F (23 °C) at 470 psi (23 °C) | 180 °F (82 °C) at 115 psi (82 °C) | 0.94                     |
| 1-1/2" x 1" CPVC 80 Reducing Coupling (SxS)           | 9829211   | Socket 1"     | 73 °F (23 °C) at 470 psi (23 °C) | 180 °F (82 °C) at 115 psi (82 °C) | 0.29                     |
| 1-1/2" x 1-1/4" CPVC 80 Reducing Coupling (SxS)       | 9829212   | Socket 1-1/4" | 73 °F (23 °C) at 470 psi (23 °C) | 180 °F (82 °C) at 115 psi (82 °C) | 0.29                     |
| 2" x 1/2" CPVC 80 Reducing Coupling (SxS), Bushed     | 9829247FB | Socket 1/2"   | 73 °F (23 °C) at 400 psi (23 °C) | 180 °F (82 °C) at 100 psi (82 °C) | 0.3                      |
| 2" x 3/4" CPVC 80 Reducing Coupling (SxS), Bushed     | 9829248FB | Socket 3/4"   | 73 °F (23 °C) at 400 psi (23 °C) | 180 °F (82 °C) at 100 psi (82 °C) | 0.61                     |
| 2" x 1" CPVC 80 Reducing Coupling (SxS)               | 9829249   | Socket 1"     | 73 °F (23 °C) at 400 psi (23 °C) | 180 °F (82 °C) at 100 psi (82 °C) | 0.62                     |
| 2" x 1-1/4" CPVC 80 Reducing Coupling (SxS)           | 9829250   | Socket 1-1/4" | 73 °F (23 °C) at 400 psi (23 °C) | 180 °F (82 °C) at 100 psi (82 °C) | 0.71                     |
| 2" x 1-1/2" CPVC 80 Reducing Coupling (SxS)           | 9829251   | Socket 1-1/2" | 73 °F (23 °C) at 400 psi (23 °C) | 180 °F (82 °C) at 100 psi (82 °C) | 0.71                     |
| 2-1/2" x 1/2" CPVC 80 Reducing Coupling (SxS), Bushed | 9829287FB | Socket 1/2"   | 73 °F (23 °C) at 420 psi (23 °C) | 180 °F (82 °C) at 105 psi (82 °C) | 0.66                     |
| 2-1/2" x 3/4" CPVC 80 Reducing Coupling (SxS), Bushed | 9829288FB | Socket 3/4"   | 73 °F (23 °C) at 420 psi (23 °C) | 180 °F (82 °C) at 105 psi (82 °C) | 0.67                     |

|                                                             |           |               |                                  |                                   |       |
|-------------------------------------------------------------|-----------|---------------|----------------------------------|-----------------------------------|-------|
| 2-1/2" x 1" CPVC 80 Reducing Coupling (SxS), Bushed         | 9829289FB | Socket 1"     | 73 °F (23 °C) at 420 psi (23 °C) | 180 °F (82 °C) at 105 psi (82 °C) | 0.64  |
| 2-1/2" x 1-1/4" CPVC 80 Reducing Coupling (SxS), Bushed     | 9829290FB | Socket 1-1/4" | 73 °F (23 °C) at 420 psi (23 °C) | 180 °F (82 °C) at 105 psi (82 °C) | 0.59  |
| 2-1/2" x 1-1/2" CPVC 80 Reducing Coupling (SxS)             | 9829291   | Socket 1-1/2" | 73 °F (23 °C) at 420 psi (23 °C) | 180 °F (82 °C) at 105 psi (82 °C) | 0.8   |
| 2-1/2" x 2" CPVC 80 Reducing Coupling (SxS), Bushed         | 9829292FB | Socket 2"     | 73 °F (23 °C) at 420 psi (23 °C) | 180 °F (82 °C) at 105 psi (82 °C) | 1.2   |
| 3" x 1" CPVC 80 Reducing Coupling (SxS), Bushed             | 9829335FB | Socket 1"     | 73 °F (23 °C) at 370 psi (23 °C) | 180 °F (82 °C) at 90 psi (82 °C)  | 0.7   |
| 3" x 1-1/2" CPVC 80 Reducing Coupling (SxS), Bushed         | 9829337FB | Socket 1-1/2" | 73 °F (23 °C) at 370 psi (23 °C) | 180 °F (82 °C) at 90 psi (82 °C)  | 0.93  |
| 3" x 2" CPVC 80 Reducing Coupling (SxS)                     | 9829338   | Socket 2"     | 73 °F (23 °C) at 370 psi (23 °C) | 180 °F (82 °C) at 90 psi (82 °C)  | 1     |
| 3" x 2-1/2" CPVC 80 Reducing Coupling (SxS), Bushed         | 9829339FB | Socket 2-1/2" | 73 °F (23 °C) at 370 psi (23 °C) | 180 °F (82 °C) at 90 psi (82 °C)  | 1.56  |
| 4" x 1" CPVC 80 Reducing Coupling (SxS), Bushed             | 9829417FB | Socket 1"     | 73 °F (23 °C) at 320 psi (23 °C) | 180 °F (82 °C) at 80 psi (82 °C)  | 2.43  |
| 4" x 1-1/2" CPVC 80 Reducing Coupling (SxS), Bushed         | 9829419FB | Socket 1-1/2" | 73 °F (23 °C) at 320 psi (23 °C) | 180 °F (82 °C) at 80 psi (82 °C)  | 2.56  |
| 4" x 2" CPVC 80 Reducing Coupling (SxS), Bushed             | 9829420FB | Socket 2"     | 73 °F (23 °C) at 320 psi (23 °C) | 180 °F (82 °C) at 80 psi (82 °C)  | 2.61  |
| 4" x 2-1/2" CPVC 80 Reducing Coupling (SxS), Bushed         | 9829421FB | Socket 2-1/2" | 73 °F (23 °C) at 320 psi (23 °C) | 180 °F (82 °C) at 80 psi (82 °C)  | 2.33  |
| 4" x 3" CPVC 80 Reducing Coupling (SxS)                     | 9829422   | Socket 3"     | 73 °F (23 °C) at 320 psi (23 °C) | 180 °F (82 °C) at 80 psi (82 °C)  | 1.82  |
| 6" x 1-1/2" CPVC 80 Reducing Coupling (SxS), Bushed, 3 Step | 9829527FB | Socket 1-1/2" | 73 °F (23 °C) at 280 psi (23 °C) | 180 °F (82 °C) at 70 psi (82 °C)  | 8.23  |
| 6" x 2" CPVC 80 Reducing Coupling (SxS), Bushed             | 9829528FB | Socket 2"     | 73 °F (23 °C) at 280 psi (23 °C) | 180 °F (82 °C) at 70 psi (82 °C)  | 2.09  |
| 6" x 2-1/2" CPVC 80 Reducing Coupling (SxS), Bushed, 2 Step | 9829529FB | Socket 2-1/2" | 73 °F (23 °C) at 280 psi (23 °C) | 180 °F (82 °C) at 70 psi (82 °C)  | 8.23  |
| 6" x 3" CPVC 80 Reducing Coupling (SxS), Bushed             | 9829530FB | Socket 3"     | 73 °F (23 °C) at 280 psi (23 °C) | 180 °F (82 °C) at 70 psi (82 °C)  | 8.23  |
| 6" x 4" CPVC 80 Reducing Coupling (SxS)                     | 9829532   | Socket 4"     | 73 °F (23 °C) at 280 psi (23 °C) | 180 °F (82 °C) at 70 psi (82 °C)  | 7.3   |
| 8" x 4" CPVC 80 Reducing Coupling (SxS), Bushed             | 9829582FB | Socket 4"     | 73 °F (23 °C) at 250 psi (23 °C) | 180 °F (82 °C) at 60 psi (82 °C)  | 13.44 |
| 8" x 6" CPVC 80 Reducing Coupling (SxS)                     | 9829585   | Socket 6"     | 73 °F (23 °C) at 250 psi (23 °C) | 180 °F (82 °C) at 60 psi (82 °C)  | 8.23  |

| Part name                                                                       | Part no.  | Codes                        | Standards                             | Listings                   |
|---------------------------------------------------------------------------------|-----------|------------------------------|---------------------------------------|----------------------------|
| ChlorFIT Acoplamiento de Accesorios Reductores                                  | All       | UPC IBC IRC IPC UMC NSPC IMC | ASTM F439 NSF/ANSI/CAN 61 NSF/ANSI 14 | ULC NSFpw-G IAPMO U.P.Code |
| In addition, the following parts have additional codes, standards, or listings: |           |                              |                                       |                            |
| 3/4" x 1/2" CPVC 80 Reducing Coupling (SxS)                                     | 9829101   |                              |                                       | ICC-ES-PMG                 |
| 1" x 1/2" CPVC 80 Reducing Coupling (SxS)                                       | 9829130   |                              |                                       | ICC-ES-PMG                 |
| 1" x 3/4" CPVC 80 Reducing Coupling (SxS)                                       | 9829131   |                              |                                       | ICC-ES-PMG                 |
| 1-1/4" x 3/4" CPVC 80 Reducing Coupling (SxS), Bushed                           | 9829167FB |                              |                                       | ICC-ES-PMG                 |
| 1-1/4" x 1" CPVC 80 Reducing Coupling (SxS), Bushed                             | 9829168FB |                              |                                       | ICC-ES-PMG                 |
| 1-1/2" x 1/2" CPVC 80 Reducing Coupling (SxS), Bushed                           | 9829209FB |                              |                                       | ICC-ES-PMG                 |
| 1-1/2" x 3/4" CPVC 80 Reducing Coupling (SxS), Bushed                           | 9829210FB |                              |                                       | ICC-ES-PMG                 |
| 1-1/2" x 1" CPVC 80 Reducing Coupling (SxS)                                     | 9829211   |                              |                                       | ICC-ES-PMG                 |
| 1-1/2" x 1-1/4" CPVC 80 Reducing Coupling (SxS)                                 | 9829212   |                              |                                       | ICC-ES-PMG                 |
| 2" x 1/2" CPVC 80 Reducing Coupling (SxS), Bushed                               | 9829247FB |                              |                                       | ICC-ES-PMG                 |
| 2" x 3/4" CPVC 80 Reducing Coupling (SxS), Bushed                               | 9829248FB |                              |                                       | ICC-ES-PMG                 |
| 2" x 1" CPVC 80 Reducing Coupling                                               | 9829249   |                              |                                       | ICC-ES-PMG                 |

| (SxS)                                                       |           |            |
|-------------------------------------------------------------|-----------|------------|
| 2" x 1-1/4" CPVC 80 Reducing Coupling (SxS)                 | 9829250   | ICC-ES-PMG |
| 2" x 1-1/2" CPVC 80 Reducing Coupling (SxS)                 | 9829251   | ICC-ES-PMG |
| 2-1/2" x 1/2" CPVC 80 Reducing Coupling (SxS), Bushed       | 9829287FB | ICC-ES-PMG |
| 2-1/2" x 3/4" CPVC 80 Reducing Coupling (SxS), Bushed       | 9829288FB | ICC-ES-PMG |
| 2-1/2" x 1" CPVC 80 Reducing Coupling (SxS), Bushed         | 9829289FB | ICC-ES-PMG |
| 2-1/2" x 1-1/4" CPVC 80 Reducing Coupling (SxS), Bushed     | 9829290FB | ICC-ES-PMG |
| 2-1/2" x 1-1/2" CPVC 80 Reducing Coupling (SxS)             | 9829291   | ICC-ES-PMG |
| 2-1/2" x 2" CPVC 80 Reducing Coupling (SxS), Bushed         | 9829292FB | ICC-ES-PMG |
| 3" x 1" CPVC 80 Reducing Coupling (SxS), Bushed             | 9829335FB | ICC-ES-PMG |
| 3" x 1-1/2" CPVC 80 Reducing Coupling (SxS), Bushed         | 9829337FB | ICC-ES-PMG |
| 3" x 2" CPVC 80 Reducing Coupling (SxS)                     | 9829338   | ICC-ES-PMG |
| 3" x 2-1/2" CPVC 80 Reducing Coupling (SxS), Bushed         | 9829339FB | ICC-ES-PMG |
| 4" x 1" CPVC 80 Reducing Coupling (SxS), Bushed             | 9829417FB | ICC-ES-PMG |
| 4" x 1-1/2" CPVC 80 Reducing Coupling (SxS), Bushed         | 9829419FB | ICC-ES-PMG |
| 4" x 2" CPVC 80 Reducing Coupling (SxS), Bushed             | 9829420FB | ICC-ES-PMG |
| 4" x 2-1/2" CPVC 80 Reducing Coupling (SxS), Bushed         | 9829421FB | ICC-ES-PMG |
| 4" x 3" CPVC 80 Reducing Coupling (SxS)                     | 9829422   | ICC-ES-PMG |
| 6" x 1-1/2" CPVC 80 Reducing Coupling (SxS), Bushed, 3 Step | 9829527FB | ICC-ES-PMG |
| 6" x 2" CPVC 80 Reducing Coupling (SxS), Bushed             | 9829528FB | ICC-ES-PMG |
| 6" x 2-1/2" CPVC 80 Reducing Coupling (SxS), Bushed, 2 Step | 9829529FB | ICC-ES-PMG |
| 6" x 3" CPVC 80 Reducing Coupling (SxS), Bushed             | 9829530FB | ICC-ES-PMG |
| 6" x 4" CPVC 80 Reducing Coupling (SxS)                     | 9829532   | ICC-ES-PMG |

| Installation                                                                                                                                                                                                                                                                                                           | Related applications                   |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|
| Realice las conexiones mediante soldadura con solvente utilizando imprimación y cemento solvente diseñado específicamente para tuberías y accesorios de CPVC Cédula 80. Consulte el Manual de Uponor ChlorFIT o la Hoja de instrucciones de soldadura con solvente de Uponor ChlorFIT para obtener detalles completos. | Agua doméstica<br>Tuberías hidráulicas |

| Footnotes | Contact information                                                                                                                                                                                                       |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| -         | <p>Uponor Inc.<br/>5925 148th Street West<br/>Apple Valley, MN 55124<br/>T 800.321.4739<br/>F 952.891.2008</p> <p>Uponor Ltd.<br/>6510 Kennedy Road<br/>Mississauga, ON L5T 2X4<br/>T 888.594.7726<br/>F 800.638.9517</p> |