

Tapas ChlorFIT

Project Information

Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

Technical data

Material CPVC

Product information and application use

Utilice los tapones de CPVC Corzan® ChlorFIT® Schedule 80 de Uponor en sistemas de agua potable fría y caliente, así como en aplicaciones de calefacción y refrigeración hidráulicas.



Part name	Part no.	A [inc h]	B [inc h]	C [inc h]	D [inc h]	E [inc h]	End Type 1	Operating Temperature 1 [°F]	Operating Temperature 2 [°F]	Weight per UOM [lbs/UOM]
1/2" CPVC80 Cap (S)	9847005	1.295	0.84	1.289	0.882	0.648	CPVC 1/2"	73 °F (23 °C) at 850 psi (23 °C)	180 °F (82 °C) at 210 psi (82 °C)	0.06
3/4" CPVC80 Cap (S)	9847007	1.465	1.05	1.459	1.008	0.733	CPVC 3/4"	73 °F (23 °C) at 690 psi (23 °C)	180 °F (82 °C) at 170 psi (82 °C)	0.07
1" CPVC80 Cap (S)	9847010	1.825	1.315	1.67	1.133	0.913	CPVC 1"	73 °F (23 °C) at 630 psi (23 °C)	180 °F (82 °C) at 155 psi (82 °C)	0.12
1 1/4" CPVC80 Cap (S)	9847012	2.215	1.66	1.88	1.258	1.107	CPVC 1-1/4"	73 °F (23 °C) at 520 psi (23 °C)	180 °F (82 °C) at 130 psi (82 °C)	0.19
1 1/2" CPVC80 Cap (S)	9847015	2.6	1.9	2.087	1.383	1.3	CPVC 1-1/2"	73 °F (23 °C) at 470 psi (23 °C)	180 °F (82 °C) at 115 psi (82 °C)	0.29
2" CPVC80 Cap (S)	9847020	3.015	2.375	2.317	1.509	1.507	CPVC 2"	73 °F (23 °C) at 400 psi (23 °C)	180 °F (82 °C) at 100 psi (82 °C)	0.37
2-1/2" CPVC80 Cap (S)	9847025	3.448	2.875	2.726	1.775	1.724	CPVC 2-1/2"	73 °F (23 °C) at 420 psi (23 °C)	180 °F (82 °C) at 105 psi (82 °C)	0.64
3" CPVC80 Cap (S)	9847030	4.142	3.5	3.051	1.9	2.071	CPVC 3"	73 °F (23 °C) at 370 psi (23 °C)	180 °F (82 °C) at 90 psi (82 °C)	0.83
4" CPVC80 Cap (S)	9847040	5.2	4.5	3.674	2.328	2.6	CPVC 4"	73 °F (23 °C) at 320 psi (23 °C)	180 °F (82 °C) at 80 psi (82 °C)	1.56
6" CPVC80 Cap (S)	9847060	7.56	6.625	4.932	3.04	3.78	CPVC 6"	73 °F (23 °C) at 280 psi (23 °C)	180 °F (82 °C) at 70 psi (82 °C)	3.01
8" CPVC80 Cap (S)	9847080	9.74	8.625	6.301	4.02	4.87	CPVC 8"	73 °F (23 °C) at 250 psi (23 °C)	180 °F (82 °C) at 60 psi (82 °C)	6.22

Part name	Part no.	Codes	Standards	Listings
Tapas ChlorFIT	All	UPC IBC IRC IPC UMC NSPC IMC	ASTM F439 NSF/ANSI/CAN 61 NSF/ANSI 14	ULC NSFpw-G APMO U.P.Code

In addition, the following parts have additional codes, standards, or listings:

1/2" CPVC80 Cap (S)	9847005			ICC-ES-PMG
3/4" CPVC80 Cap (S)	9847007			ICC-ES-PMG
1" CPVC80 Cap (S)	9847010			ICC-ES-PMG
1 1/4" CPVC80 Cap (S)	9847012			ICC-ES-PMG
1 1/2" CPVC80 Cap (S)	9847015			ICC-ES-PMG
2" CPVC80 Cap (S)	9847020			ICC-ES-PMG
2-1/2" CPVC80 Cap (S)	9847025			ICC-ES-PMG
3" CPVC80 Cap (S)	9847030			ICC-ES-PMG
4" CPVC80 Cap (S)	9847040			ICC-ES-PMG
6" CPVC80 Cap (S)	9847060			ICC-ES-PMG

Installation	Related applications
Realice las conexiones mediante soldadura con solvente utilizando imprimación y cemento solvente diseñado específicamente para tuberías y accesorios de CPVC Cédula 80. Consulte el Manual de Uponor ChlorFIT o la Hoja de instrucciones de soldadura con solvente de Uponor ChlorFIT para obtener detalles completos.	Agua doméstica Tuberías hidráulicas

Footnotes	Contact information
-	<p>Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008</p> <p>Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517</p>