

Referenssit

## Jugendstil Villa in Leipzig



### Uponorin osallistuminen



235 m<sup>2</sup>

## Jugendstil Villa in Leipzig

Comfort and energy efficiency versus protection of historical structures. Squaring the circle in a Jugendstil villa in Leipzig.

### Projektin tiedot

Location

Leipzig, Germany

Valmistuminen

2013

Rakennustyyppi

Pientalo

Product systems

Lattialämmitys ja -viilennys

Osoite

Demmeringstraße 34

Projektityyppi

Renovation

## Yhteistyössä mukana

### Clients:

Katja Czogalla  
Demmeringstraße 34  
04179 Leipzig

Stefan Preiß  
Im Laichle 9/1  
73527 Schwäbisch Gmünd

### Architect:

Katja Czogalla  
Demmeringstraße 34  
04179 Leipzig

### Installers:

[SHK Berger](#)  
Burkhardtsdorfer Str. 7  
09221 Neukirchen-Adorf

### Energy concept:

[Preiß Energieberatung](#)  
Im Laichle 9/1  
73527 Schwäbisch Gmünd

---

## Renovation solution with efficiency and comfort

With a floor space of about 235 m<sup>2</sup>, the building is a successful example of how intelligent solutions can be used to transform a disused property into a real gem that satisfies the criteria for a Reconstruction Loan Corporation (Kreditanstalt für Wiederaufbau, KfW) subsidized efficiency project without visible intervention in the protected structure. In addition to improved fire safety and noise-proofing measures, a superior living standard is achieved through the innovative energy concept.

In close consultation with energy consultants Preiss and the specialists at Uponor, the building consortium decided to control the building's temperature with various radiant heating system as part of the renovation project.

This meant that part of the historical tiled floors could be preserved. There was no need to create additional installation shafts. In the attic, too, the moisture-sensitive wooden beams are protected from condensation by the radiant heat. This can prevent heat bridges and the associated increased risk of mould.

### Surface heating systems Siccus, Minitec and Renovis by Uponor

The Uponor drywall system Uponor Siccus was used on the ground floor and first floor, while the Minitec wet plaster system was used on the wall of the mezzanine. Furthermore, on the first floor, Uponor Renovis was installed on the wall in the stairwell and in the bathroom and on the ceiling in the bedroom. Architect and developer Katja Czogalla chose a ceiling

heating system for the attic with the new Renovis renovation system from Uponor. First the existing roof was given an energy upgrade with insulation placed both between and under the rafters.

Measuring approximately 90 m<sup>2</sup>, the apartment in the attic is heated with 36 Renovis 2000 x 625 mm panels, 14 1200 x 625 mm panels and 14 800 x 625 mm panels.

Following the installation of the substructure and panels, the installers connected the pipes to the ring lines of high-pressure cross-linked PE-Xa pipe, dimensions 20 x 2 mm, using Quick & Easy technology and linked them to the Tichelmann distributor.

After the leak test, the joints between the panels were filled and sanded. Work could then continue immediately on the Renovis elements.

Surface heating reduces energy costs

Because of its low pipe coverage, drywall ceiling heating allow particularly low supply temperatures. When heat is required, the elements in the attic of the Jugendstil villa are operated with a supply temperature of 41.9 ° C and a return temperature of 33.6 ° C. The energy for the building, with a standard heat load of 17.2 kW, is generated by an air-to-water heat pump. Water heating is supported by a thermal solar system.

## Jugendstil Villa in Leipzig





**uponor**

Uponor Infra Oy

Uponor Infra Oy  
Uponor Suomi Oy  
Kouvolaantie 365, 15550 Nastola  
Kappelinmäentie 240, 65370 Vaasa

Puhelin +358 20 129 211  
Sähköposti  
asiakaspalvelu@uponor.com  
W www.uponor.com